

ICON™

A LANDOLL® Company

6510 CONSTRUCTION DISC



6510 CONSTRUCTION DISC

Designed with the user in mind, for maximum durability with less maintenance for less down time.

Durability

- 8" x 8" x 1/2" and 8" x 6" x 1/2" Ridged Frame Construction
- HD Welded Hydraulic Cylinders (2) 4 1/2 x 8 (1) 4 1/2 x 12
- 2 3/4" HD Gang Bolts
- 32" x 10 mm Notched Disc Blades
- 4000 psi Hydraulic Hoses
- 32/1550 x 16.5 SL Tires, with 8 Bolt Wheels and 3" Slip in Spindles
- Heavy Duty Scraper Blades
- Heavy Duty Triple Sealed Bearings
- Maintenance Free Rock Shaft Pivot Bushings

Operator Friendly

- Hydraulic Adjustable on the Fly Draft System
- Hydraulic Leveling System
- 360° Swivel Pintle Hitch
- 719 Pounds per Blade for Easy Penetration

Other Specifications

- 17 1/2" Blade Spacing
- 20° Front Blade Angle
- 18° Rear Blade Angle
- 11" Disc Blade Clearance
- 15" Penetration Depth
- 10' 9" Working Width
- 11' 6" Transportation Width
- 11,500 Weight



ICON INDUSTRIES

1600 W. 8th Street • Beloit, KS 67420 • (785) 738-3547 • www.iconindinc.com