



DXB130H | Hydraulic Breaker






DXB130H – Make every blow count!

Doosan hydraulic breakers offer powerful performance and top productivity. Whether you are demolishing concrete, cutting asphalt or breaking rocks, Doosan hydraulic breakers are designed to give you top productivity to make each blow count. Doosan breakers provide high performance, simple and reliable design, low maintenance cost and carrier protection.

Breaker package includes :

- 2 hydraulic hoses (2500 mm long with ORFS couplers)
- 1 moil point and 1 wedge chisel
- Sound-reducing housing
- Nitrogen charge kit
- Tool box
- User and installation manual
- CE certification
- Doosan engineering approval
- One year warranty
- Automatic greaser (optional)



Energy recovery system

- The energy recovery system increases the striking power by using the energy generated when the piston rebounds.
- When the breaker is used on hard materials, the energy recovery system automatically increases the breaker frequency to optimize performance.

Unique valve system

- The patented main valve controls the piston movement in order to optimize the striking power.


High quality piston and cylinder

- The piston and cylinder are made of similar steel with the highest quality
 materials used in the European aerospace industry. The number of wear
 parts such as the piston and cylinder has been minimized to reduce
 replacement and maintenance cost.
- Fine tolerances minimize internal leaks and increase breaker efficiency.

Blank fire protection

- A hydraulic cushion at the bottom of the cylinder bore slows and stops the downward movement of the piston.
- The dampening system protects against blank firing from the first blow.

Breaker Package and Options			Part Number
DXB130H brea	aker		86732690
Automatic greaser (optional)			86731833
Compatible Carriers			Fixing Cap Kit*
DX160LC/W			86727815
DX170W			86727823
DX180LC			86727831
DX190W			86727831
DX210W			86727831
* Pin-on fixing	cap kit includes bolt	s to mount the bre	aker.
Points and Cl	nisels		
Moil point**			86723632
Wedge chisel (cross)**			86725652
Blunt			86725678
Pyramidal			86725660
** included in b	oreaker kit		
Specifications		Unit	
Carrier weight		t	15 - 22
Operating weight		kg	1090
Tool diameter		mm	124
Operating pressure		bar	170
Max. average back pressure		bar	20
Flow	Min.	l/min	90
	Max.	l/min	140
Frequency		blows/min	650
Energy / blow		J	2700
Noise level		dB(A)	124





ß

ofc

mm

Energy / blow J Noise level dB(A)

Doosan Infracore Construction Equipment - Drève Richelle 167 - B-1410 Waterloo, Belgium