HEAVY DUTY PERFORMANCE CHEMICALS



ANYWHERE. ANYTIME. ANY ENGINE."

# Prestone Command<sup>™</sup> DEF Diesel Exhaust Fluid



Prestone Command<sup>™</sup> Diesel Exhaust Fluid (DEF) is formulated with high quality urea and pure demineralized water to work with ALL Selective Catalytic Reduction (SCR)-equipped diesel engines. Prestone Command<sup>™</sup> Diesel Exhaust Fluid (DEF) is a nontoxic solution of 67.5% water and 32.5% automotive grade urea. It is a stable fluid that is colorless and odorless. Prestone Command<sup>™</sup> DEF usage will vary by vehicle. Most OEMs claim usage will equal to 2%-3% of diesel fuel consumption. On average, this amounts to one gallon of DEF to every 50-75 gallons of fuel. Check owner's manual for proper usage in your vehicle. DEF does not require special handling. DEF reacts with certain metals such as aluminum, copper and brass. Therefore, only place DEF in storage tanks and dispensing equipment made of stainless steel or high density polyethylene.

DEF is a consumable component of SCR equipped trucks. SCR allows the engine manufacture to tune the engine for increased fuel efficiency while remaining in compliance with Federal emissions requirements.

# APPROVED FOR SCR-EQUIPPED<br/>ENGINESSAFE AND EASY TO HANDLEEXCEPTIONAL QUALITY• Non-Flammable• Stored and Handled<br/>per ISO 22241-1<br/>Guidelines• Non Toxic• Stored and Handled<br/>per ISO 22241-1<br/>Guidelines• Premixed with Pure<br/>Water• Batch Date Coded• Long Shelf Life• Packaged on<br/>Dedicated Equipment

Specifications and Performance: Prestone<sup>®</sup> Command<sup>™</sup> DEF meets all API and ISO2224-1 specifications.

for Purity

HD1001 HD1000-55 HD1000-330

Stock #

HD1000

UPC Code 797496876997 797496877031 797496877889 797496877896

**Pack** 1 gal. 2.5 gal. 55 gal. 330 gal. tote

Questions/Comments go to www.prestonecommand.com Reference recycle information from label. Made in U.S.A.



#### ANYWHERE. ANYTIME. ANY ENGINE.™

# PRESTONE COMMAND<sup>™</sup> DEF DIESEL EXHAUST FLUID

## **FEATURES & BENEFITS**

SAFE AND EASY TO HANDLE, Non-Flammable, Non Toxic, Premixed with Pure Water, Long Shelf Life

EXCEPTIONAL QUALITY, Stored and Handled per ISO 22241-1 Guidelines, Batch Date Coded, Packaged on Dedicated Equipment for Purity

## DIRECTIONS

Prestone Command<sup>™</sup> DEF usage will vary by vehicle. Most OEM's claim usage will equal to 2%-3% of diesel fuel consumption. On average, this amounts to one gallon of DEF to every 50-75 gallons of fuel. Check owner's manual for proper usage in your vehicle. DEF does not require special handling. DEF reacts with certain metals such as aluminum, copper and brass. Therefore, only place DEF in storage tanks and dispensing equipment made of stainless steel or high density polyethylene.

Para instrucciones en español, visite www.PrestoneCommand.com

#### **APPROVED FOR SCR-EQUIPPED ENGINES**

#### Safe and Easy to Handle

# Exceptional Quality

- Non-Flammable
- Stored and Handled per
- Non Toxic
- Premixed with Pure Water
- Long Shelf Life
- Batch Date Coded
  Packaged on Dedicated Equipment for Purity

ISO 22241-1 Guidelines

#### CAUTION

Contains: Demineralized Water, Automotive Grade Urea

# **KEEP OUT OF THE REACH OF CHILDREN**

#### PRECAUTIONARY MEASURES

DEF should be stored in temperatures between 12 and 80 degrees F and in a dry, well-ventilated area. It should also be stored out of direct sunlight. Exposures to higher temperatures for short periods of time should not impact the quality of the product.

FIRST AID TREATMENT: If in eyes: If irritation or redness develops, move away from exposure and into fresh air. Flush eyes with clean water. If symptoms persist, seek medical attention. If on skin: Remove affected shoes and clothing and cleanse area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention. If vapors are inhaled: Remove to fresh air. If breathing difficulty occurs or persists, seek medical attention. If ingested: Do NOT induce vomiting. Seek medical attention if symptoms develop.

**If In Eyes:** If irritation or redness develops, move away from exposure and into fresh air. Flush eyes with clean water. If symptoms persist, seek medical attention.

**If On Skin:** Remove affected shoes and clothing and cleanse area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention. If Vapors are Inhaled: Remove to fresh air. If breathing difficulty occurs or persists, seek medical attention. If Ingested: Do NOT induce vomiting. Seek medical attention if symptoms develop.



API Certified for assured quality

Questions/Comments go to www.prestonecommand.com Reference recycle information from label. Made in U.S.A.

™ Property of Prestone Products Corporation PRESTONE PRODUCTS CORPORATION, 1900 West Field Court, Lake Forest, IL 60045 ©2013 Prestone Products Corporation