

# Easi-POUR<sup>®</sup>

*Built like it should be...OverBuilt!*



## COMPACT 880

The Easi-Pour Compact 880 is our number one selling machine. The Compact trims and pours desired configurations simultaneously and is the highest production, longest lasting machine in its class on the market today. The Compact boasts unparalleled capabilities of barrier wall to 42" high, flat work to 8' wide and everything in between. The Compact holds an incredible 1.75 cubic yards of concrete in the closeable hopper which means you can choose exactly where you want to start and stop pouring. The Compact can be ordered in track or rubber wheel designs. If you are looking to flat-out pour concrete this is the machine for you.

### 880 SPECIFICATIONS\*

#### ENGINE OPTIONS

Cummins QSB4.5 115HP John Deere 4045 T 115HP

#### CONVEYOR LOAD SYSTEM

Hydraulically driven 18" x 12' long variable speed with hydraulic raise and lower control

#### HOPPER WITH AUGER

Capacity 1 3/4 cubic yards (1.34 cubic meters)

#### WHEEL DRIVES

Borg Warner No. 6 or No. 8

#### TIRES

Firestone 15 x 19.5 Super Traction Duplex 12 ply tubeless

#### TRACKS

Hydraulically powered track system with enclosed planetary drive

Track length: 61.5" (1.5m) Pad width: 12" (305mm)

#### SENSING SYSTEM

One String line guides Easi-Pour's sensing system to automatically assure precise steering and elevation incorporating 5 OverBuilt Sensors (MFD by OverBuilt Paving & Mining) 2-steering, 2-elevation, and 1 cross-level slope sensor

#### VIBRATORS

4 Vibrator Circuits & Controls

Each Hydraulic Circuit Controlled Independently

3 Hydraulic Vibrators Standard

4 Additional Circuits Optional

#### TRIMMERS

Standard width 51" (1.3m)

Maximum width available 6' 5" (1.98m)

Depth of cut - 6" (152mm)

Replaceable carbide tipped cutting teeth

Sliding Capabilities:

16" (409mm) Vertical 30" (762mm) Horizontal

#### OPERATING SPEEDS

Paving 0'-65' per minute (20 mpm)

Overdrive Travel 0'-170' per minute (52 mpm)

#### RADIUS CAPABILITIES

Standard machine - minimum 9' radius (2.75 m)

With radius package minimum radius on L-shaped curb 3' (.91 m) on ribbon curb 2' (.61 m)

#### FUEL TANK

70 gallons (265 liters)

#### OIL RESERVOIR

70 gallons (265 liters)

#### DIMENSIONS

Length: 23' 4" (7.12 m) includes conveyor

Height: 6' 8" (2.03 m)

Width: 8' (2.4 m) transport shipping width

#### OPERATING WEIGHT

Rubber tire - 21,900 lbs. (9,933 kg)

Track Mounted - 24,000 lbs. (10,886 kg)

\* Specifications subject to change

**OverBuilt**  
PAVING & MINING

### OVERBUILT PAVING & MINING, INC.

550 Nevada Ave SW • Huron, SD 57350

(800) 368-8920 • (605) 352-1412 • (605) 352-1608 Fax • [www.overbuilt paving.com](http://www.overbuilt paving.com)

Manufacturers of EASI-POUR, EASI-MINER and EASI-GRADE



# Easi-POUR®

*Built like it should be...OverBuilt!*



**OverBuilt**  
PAVING & MINING

## OVERBUILT PAVING & MINING, INC.

550 Nevada Ave SW • Huron, SD 57350

(800) 368-8920 • (605) 352-1412 • (605) 352-1608 Fax • [www.overbuiltpaving.com](http://www.overbuiltpaving.com)

Manufacturers of EASI-POUR, EASI-MINER and EASI-GRADE