



THE VERMEER DEALER NETWORK:
RELIABLE SUPPORT, ALL OVER THE WORLD.



Vermeer Asia Pacific
Singapore 608586
Phone: +65 6516 9560
Fax: +65 6515 9218

Vermeer Corporation
Pella, Iowa 50219 U.S.A.
Phone: (641) 628-3141

Vermeer Latin America
Valinhos, SP - Brazil
Phone: +55 19 3881-3848
Fax: +55 19 3881-3848, ext. 108

Vermeer EMEA
(Europe, Middle East, Africa and CIS)
the Netherlands
Phone: +31 113 272700
Fax: +31 113 272727

Call toll-free 1-888-VERMEER
1-888-837-6337 (USA only)
www.vermeer.com

A GLOBAL INITIATIVE

Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Vermeer and the Vermeer logo are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. © 2012 Vermeer Corporation. All Rights Reserved.

**1 YEAR
1000 HOUR
WARRANTY**

BC900XL BRUSH CHIPPER



BC900XL BRUSH CHIPPER



A chipper that doesn't play games.

Chuck and duck sounds like a bad school yard game – but when out chipping, the last thing you want to do is leave your safety to chance. That is why the new Vermeer BC900XL brush chipper was designed to eliminate the guesswork out of chipping. No chucking. No ducking. Just smooth chipping performance.

Able to chip heavily branched material up to 9" (23 cm) in diameter and 14" (35.5 cm) wide, the BC900XL is ideal for line clearing and general clean-up needs. In combination, the Vermeer exclusive SmartFeed system, and its 40 hp (29.8 kW) Kohler engine, pulls in and processes difficult material. Standard safety features such as an upper and bottom feed stop bar, keep operators safe while chipping.

Whether purchasing your first chipper, stocking a rental yard or adding to a fleet, the Vermeer BC900XL brush chipper is soon to be the preferred choice.



1: 40 hp (29.8 kW) Kohler gas engine. The BC900XL is equipped with a Kohler Command CH1000 gas engine with no-spill oil filter change, providing 40 hp (29.8 kW) to process branches and ease of serviceability.

2: Operator safety. Combined with the patented bottom feed stop bar is the four-position upper feed control bar with dual stop positions and forward/reverse feed positions. Mounted over the feed table, it enables the operator to stop the feed rollers and select forward or reverse operations. Dual reset/hold-to-run buttons allow the operator to readily reset the bottom feed stop bar.

3: The patented SmartFeed system helps increase operator productivity while reducing strain on vital engine parts. The feed-sensing control system monitors engine rpm and automatically stops and reverses the feed roller when feeding larger, hardwood material.

4: The 1-year/1000-hour limited warranty offers you peace of mind.



5: A large rectangular 9" x 14" (23 cm x 35.6 cm) feed opening helps boost productivity by reducing the need to trim heavily branched material before feeding it into the chipper.

BC900XL SPECIFICATIONS

GENERAL

Weight: 2920 lb (1324.5 kg)

Transport length (feed table up, tongue in): 11.7' (3.6 m)

Transport width: 79.5" (201.9 cm)

Transport height: 101.5" (257.8 cm)

ENGINE

Make and model: Kohler Command CH1000

Horsepower: 40 hp (29.8 kW)

Max torque: 61.5 ft-lb (83.4 Nm)

Fuel type: Gas

Number of cylinders: 2

Cooling medium: Liquid

CAPACITIES

Fuel tank: 15 gal (56.8 L)

Hydraulic tank: 6.8 gal (25.7 L)

CUTTING SYSTEM

Disc size: 33" dia. x 1" wide (83.8 cm dia. x 2.5 cm)

Speed: 1400 rpm

Knives: Two A8 chipper steel

Shear bar: Two usable edges

FEED/DISCHARGE SYSTEM

Infeed throat/feed capacity: 9" x 14" (23 cm x 35.6 cm)

Infeed opening: 32" x 46" (81.3 cm x 116.8 cm)

Feed table length: 25" (63.5 cm)

Feed table height: 29.5" (74.9 cm)

Feed roller style: Single horizontal

Infeed rate: 140 fpm (42.7 m/min)

CHASSIS

Frame: 3/16" x 5.6" (.5 cm x 14.2 cm) Z channel

Tires: ST215/75R14 Load Range C

Axle/Suspension: 3500 lb (1587.6 kg) rubber torsion

ELECTRICAL

System voltage: 12 V

Lights: LED stop, turn, tail, license