



SPECIFICATIONS, UTILIGUARD

RECEIVER	U.S.	METRIC
DIMENSIONS		
Height, max	27.2 in	705 mm
Length, max	12.8 in	325 mm
Width, max	4.75 in	150 mm
Operating weight, max	4.8 lb	2.2 kg
ENVIRONMENTAL		
Operating temperature	-4-122°F	-20-50°C
Storage temperature	-25-158°F	-32-70°C
IP rating	IP65	
PERFORMANCE		
Depth estimate tolerances*		
Active line	± 5%-10 ft	± 5%-3 m
Passive line	± 10%-10 ft	± 10%-3 m
Beacon	± 5%-10 ft	± 5%-3 m
BATTERY		
Battery type	D-Cell selectable alkaline or commercially available NiMH	
Number of cells	2	
Battery life, max	30 hrs	

* Locators are calibrated, at factory frequencies, to these tolerances under ideal test conditions. Actual operating conditions may have signal distortions or noise sources, which result in depth estimate errors.

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

TRANSMITTER	U.S.	METRIC
DIMENSIONS		
Height, max	10 in	254 mm
Length, max	12 in	381 mm
Width, max	7.75 in	152 mm
Operating weight, max	7.7 lb	3.4 kg
ENVIRONMENTAL		
Operating temperature	-4-122°F	-20-50°C
Storage temperature	-25-158°F	-32-70°C
IP rating	IP65	
BATTERY		
Battery type	Standard D-cell alkaline; optional rechargeable Li-ion pack	
Number of cells	10	
Battery life		
Alkaline	100 hrs	
Li-ion	80 hrs	