



# SKID STEER LOADER

**4200V**



## KEY FEATURES

- ▲ Low Effort Joystick Controls
- ▲ Air Suspension Seat
- ▲ Cab Enclosure with Heat and Air Conditioning
- ▲ High Flow Auxiliary Hydraulics
- ▲ 2 Travel Speeds
- ▲ Power-A-Tach Quick Coupler
- ▲ Selectable Self Level
- ▲ Load Sensing Hydraulic System

## KEY SPECIFICATIONS

- ▲ Operating capacity (50%) – 4,200 lbs. (1906 kg)
- ▲ Overall height to top of ROPS – 82" (2083 mm)
- ▲ 120.7 hp (90 kW) @ 2200 rpm Deutz engine
- ▲ Deutz / TD 3.6 EPA tier IV engine
- ▲ 354 ft.-lbs. (480 Nm) @ 1600 maximum torque
- ▲ 9,040 lbf. (40.2 kn) tilt breakout force
- ▲ 144" (3653 mm) height to hinge pin
- ▲ 81" (2057 mm) overall machine width
- ▲ 11,665 lbs. (5291 kg) operating weight

# SKID STEER LOADER

4200V



## SPECIFICATIONS

DIMENSIONS	Overall Operating Height - Fully Raised (mm)	186.8" (4744)
	Height to Hinge Pin - Fully Raised (mm)	144" (3653)
	Overall Height to Top of ROPS (mm)	82" (2083)
	Overall Length with Bucket (mm)	159" (4039) w/84" Bucket
	Dump Angle at Full Height	31°
	Dump Height (mm)	115" (2921)
	Dump Reach at Full Height (mm)	38" (965)
	Rollback at Ground	30°
	Rollback Angle at Full Height	98°
	Seat to Ground Height (mm)	41.2 (1046)
	Wheelbase (mm)	54.5" (1384)
	Overall Width - Less Bucket (mm)	81" (2057)
	Bucket Width (mm)	84" (2134)
	Ground Clearance to Chassis (mm)	7.7" (197)
	Overall Length - Less Bucket (mm)	123" (3124)
	Departure Angle	18°
	Clearance Circle - Front w/ Bucket (mm)	97.8" (2484)
Clearance Circle - Front w/o Bucket (mm)	55.5" (1410)	
Clearance Circle - Rear (mm)	74" (1880)	
Standard Specification Tire Size	14.00x17.5 HD	
CAPACITY / WEIGHTS	Rated Operating Capacity (kg)	4,200 lbs. (1905)
	UREA/DEF Tank (L)	4.0 gal (15)
	Fuel Tank (L)	38 gal. (144)
	Travel Speed - Maximum (km/hr)	11.6 mph (18.7)
	Operating Weight - Approximate (kg)	11,665 lbs. (5291)
ENGINE	Make	Deutz
	Model	TCD 3.6 Tier IV
	Gross Power (kW) @ rpm	120.7 hp (90) @ 2200
	Maximum Torque (Nm) @ rpm	354 ft.-lbs. (480) @ 1600
	Displacement (L)	221 cu. in. (3.6)
ELECTRICAL SYSTEM	Battery (CCA)	2 @ 12-volt (1500 total)
	Starter (kW)	12-volt (4)
	Alternator	12-volt 120-amp
HYDRAULICS	Auxiliary Hydraulics - Standard (L/min)	29 gpm (111)
	High-Flow Auxiliary Hydraulics - Option (L/min)	39.11 gpm (148)
	Reservoir Capacity (L)	15.9 gal (60)

## STANDARD FEATURES

- ▲ Adjustable Arm Rests/ 14-Pin Connector Control Towers
- ▲ Air Ride Suspension Seat
- ▲ Power-A-Tach® Attachment Mounting System
- ▲ Anti-Vandalism Protection
- ▲ Back-Up Alarm
- ▲ Block Heater
- ▲ Cab with Heat & Air Conditioning
- ▲ Engine Auto-Shutdown System
- ▲ Engine Glow Plugs
- ▲ Foot and Hand throttles
- ▲ Multi-function color display screens
- ▲ High-Flow Auxiliary Hydraulics
- ▲ Horn
- ▲ Hydraglide™ Ride Control
- ▲ Hydraloc Safety System
- ▲ Hydrostatic Drive - Pilot
- ▲ Load Sensing Hydraulic System
- ▲ Integral Access Plate
- ▲ Joystick Controls - Pilot
- ▲ Lift Arm Support Device
- ▲ Operator Restraint Bar
- ▲ Radio with Hands-Free Bluetooth
- ▲ Rear View Camera Ready
- ▲ ROPS/FOPS Level II Overhead Guard
- ▲ Self-Leveling Lift Action
- ▲ Sound Reduction Material
- ▲ Turbo-charged engine
- ▲ Two-speed drive
- ▲ Work Lights - Front and Rear



## OPTIONAL FEATURES

- ▲ Impact Resistant Door
- ▲ 3" Seatbelt and Shoulder Strap
- ▲ Rear View Camera
- ▲ Brake Release
- ▲ Rotating Beacon
- ▲ Easy Manager Telematics - Coming in 2018

*Mustang reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.*

*Mustang reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.*



MUSTANG MFG.

147 Indiana Avenue, West Bend, WI 53095 | Phone: (262) 334-9461