2024 SKID STEER & COMPACT TRACK LOADER spec guide

By Equipment Today

Essential Specifications and Features for Industry-Leading Equipment

Equipment TODAY®

2024 SKID STEER & COMPACT TRACK LOADER spec guide

By Equipment Today

BOBCAT

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
S70	23.5	2,892	760	94.5	9.8	R
S450	49	5,370	1,370	109.5	16.7	R
S510	55	6,208	1,790	114.5	17.1	R
S590	68	6,765	2,000	119	17.1	V
S62	68	6,884	2,100	114.5	17.6	R
S64	68	6,974	2,300	120	17.6	V
S66	74	7,154	2,400	120	17.6	V
S76	74	8,615	2,900	128.3	23.3	V
S650	74	8,061	2,690	124	23	V
S770	92	9,314	3,350	131.4	23	V
S86	105	9,728	3,400	132	23.6	V

*Bucket breakout force not provided

GEHL

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
R105	33.5	4,200	1,050	108	15	R
R135	45.59	5,256	1,350	110	17	R
R165	69.73	6,164	1,650	119	19	R
R190	69.73	6,881	1,900	121	19	R
V210	69.3	7,480	2,100	120.5	22.8	V
V230	72	7,710	2,300	121.5	22.8	V
V275	72	8,320	2,750	129	26	V
V330	72	9,090	3,300	131	24	V

*Bucket breakout force not provided

JCB

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Bucket Breakout Force (lbs.)	Arm Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	High Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
215	74	7,253	2,112	5,913	4,129	118	18.5	29.3	V
270	74	8,680	2,723	6,543	6,056	126	23	31.7	V
300	74	9,288	3,186	6,543	6,056	126	23.7	33	V
3TS-8W	74	9,859	1,347-3,208	6,329	2,798-4,661	126-159	23.7	33	R

KATO

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
AS12	21	3,016	728	1,641	100	9.25	R

KUBOTA

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force [Tilt] (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
SSV65	61.3	7,099	1,950	4,839	121.5	18	V
SSV75	71.6	8,245	2,690	5,884	128.3	20.9	V

WACKER NEUSON

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.) -50%	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
SW20	56	6,437	2,000	5,300	124	20	V
SW21	74	6,512	2,100	5,300	124	20	V
SW28	74	8,175	2,800	6,950	134.8	22.1	V
SW32	100	8,629	3,200	7,932	134.8	25.1	V

CATERPILLAR

SKID STEER

Model No.	Engine HP (net)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force [Tilt] (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
226D3	66	5,849	1,550	3,927	110.9	18	R
232D3	66	6,514	1,900	3,928	118.1	18	V
236D3	73	6,567	1,800	5,003	122.9	20	R
242D3	73	7,138	2,200	4,963	121.1	20	V
246D3	73	7,478	2,200	7,355	124.2	23	R
262D3	73	8,296	2,700	7,355	124.9	23	V
272D3	95	9,133	3,450	7,443	127.1	23	V
272D3 XE	106	9,573	3,700	7,362	128.6	23	V

MANITOU

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
1050R	33.5	4,200	1,050	108	15	R
1350R	45.59	5,256	1,350	110	17	R
1650R	69.73	6,164	1,650	119	19	R
1900R	69.73	6,881	1,900	121	19	R
2100V	69.3	7,480	2,100	120.5	22.8	V
2300V	72	7,710	2,300	121.5	22.8	V
2750V	72	8,320	2,750	129	26	V
3300V	72	9,090	3,300	131	24	V

*Bucket breakout force not provided

2024 spec guide

SKID STEER & COMPACT TRACK LOADER

By Equipment Today

JOHN DEERE

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
316GR	61	6,180	1,750	5,250	115.1	17	R
318G	61	6,542	1,945	6,000	120	17	V
320G	66	7,150	2,190	6,000	122.2	21	V
324G	70	7,700	2,690	8,750	126	21	V
330 P-Tier	95	9,930	2,950	10,500	132	25	V
334 P-Tier	115	10,264	4,000	13,800	132	25	V

CASE

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	"Rated Operating Capacity (lbs.) - 50% Tipping"	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
SR160B	57	5,645	1,600	5,270	112	18.4	R
SR175B	64	6,270	1,750	7,270	122	20.6	R
SV185B	57	6,570	1,850	5,550	120	20.6	V
SR210B	68	6,970	2,100	7,270	123	24.2	R
SR240B	68	7,400	2,400	8,680	125.1	24.2	R
SR270B	84	8,117	2,700	8,677	125.1	24.2	R
SV280B	68	8,000	2,800	8,620	129.5	24.2	V
SV340B	84	9,100	3,400	9,531	131.6	24.2	V

NEW HOLLAND

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity @ 50% (lbs.)	Bucket Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
L316	57	5,370	1,600	4,180	112	25.1	Radial
L320	64	6,470	2,000	7,300	121	25.1	Vertical
L328	68	7,895	2,800	8,620	129.4	24.2	Vertical
L334	84	9,100	3,400	8,160	131.1	24.2	Vertical

KIOTI

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
SL750	73.6	8,362	2,689	5,512	126.6	21.9	V

HYUNDAI

SKID STEER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
HS120V	69.7	8,481	5,380	6,327	127	21.9	V

ASV

SKID STEER

Model	Engine (net hp)	Operating Capacity (lbs., 50%)	Bucket Breakout Force (lbs.)	Operating Weight (lbs.)	Tip Load (lbs.)	Lift Height (Orientation) to Hinge Pin
MAX-Series RS-75	70.4	2,600	5,845	7,595	5,200	10' 5" (Radial)
MAX-Series VS-75	70.4	3,500	5,920	8,910	7,000	10 ' 10" (Vertical)

HYUNDAI

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
HT100V	69.7	9,755	6,570	6,204	126	21.9	V

CASE

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	"Rated Operating Capacity (lbs.) - 50% Tipping"	"Rated Operating Capacity (lbs.) - 35% tip-ping"	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
TR270B	68	8,270	2,700	1,890	7,270	125.1	24.2	R
TR310B	68	8,880	3,100	2,170	8,680	125.1	24.2	R
TR340B	84	10,000	3,400	2,380	8,700	126.7	24.2	R
TV370B	68	9,945	3,700	2,590	8,593	131.1	24.2	V
TV450B	84	10,610	4,500	3,150	9,188	131.6	24.2	V
TV620B	114	16,100	6,200	4,340	12,907	140.2	24.2	V

WACKER NEUSON

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	"Rated Operating Capacity (lbs.) 50% & 35%"	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
ST27	74	7,350	2,700/1,890	5,404	120	19.4	V
ST31	74	8,241	3,100/2,170	5,611	128.5	20	V
ST37	74	9,014	3,700/2,590	7,042	128.5	23	V
ST45	74	10,267	4,500/3,150	6,941	134.8	22.1	V
ST50	100	10,677	5,000/3,500	7,932	136.3	25.1	V

2024 spec guide

SKID STEER & COMPACT TRACK LOADER

By Equipment Today

BOBCAT

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force Lift Arm (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
T595	70	8,022	2,200	4,528	119	17.1	V
T64	68	8,727	2,300	4,474	120	17.6	V
T66	74	8,840	2,450	4,474	120	17.6	V
T650	74	9,113	2,570	6,900	124	23	V
T76	74	10,250	2,900	6,788	128.3	23.3	V
T740	74	10,127	3,200	6,994	131.4	23	V
T770	92	10,515	3,475	6,994	131.4	23	V
T86	105	12,393	3,800	7,160	132	23.6	V

KUBOTA

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force [Tilt] (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
SVL65-2	60	8,135	2,100	4,614	118.5	17.4	V
SVL75-3	73.2	9,190	2,490	6,191	122.7	19.2	V
SVL97-2	96.4 (gross hp)	11,299	3,200	7,961	128.5	23.1	V

KIOTI

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
TL750	73.6	9,689	2,300	5,512	130.3	21.9	V

TAKEUCHI

COMPACT TRACK LOADER

Model No.	Engine (gross hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift	High Hydraulic Flow (gpm)
TL6R	65.2	7,485	1,841	5,930	9' 6.4"	17.8	Radial	n/a
TL8R2	74.3	8,807	2,116	6,204	10' 1.2"	19.1	Radial	33.8
TL10V2	74.3	9,950	2,522	6,520	10' 4.8"	18.8	Vertical	32.8
TL12R2	111.3	12,300	2,975	8,210	10' 6"	23.2	Radial	40.4
TL12V2	111.3	12,860	4,107	7,874	10' 10"	23.2	Vertical	40.4

2024 SKID STEER & COMPACT TRACK LOADER spec guide

By Equipment Today

YANMAR

COMPACT TRACK LOADER

Model No.	Engine (gross hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
TL100VS	103.5	10,555	3,780	8,500	132	23	V

*Bucket breakout force with foundry bucket

GEHL

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
RT105	34	4720	1,499	109	14.5	R
RT135	46	6510	1,929	110	16.8	R
RT165	69	8020	2,357	120	13.65	R
VT210	69.3	8865	3,000	121	22.8	V
VT230	72	9250	3,286	121	22.8	V
VT275	72	10051	3,929	129.5	26	V

*Bucket breakout force not provided

NEW HOLLAND

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity @ 50% (lbs.)	Bucket Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
C327	68	8,270	2,700	7,270	125	24.2	Radial
C330	64	8,380	3,000	7,300	121	30.6	Vertical
C332	68	9,630	3,200	7,360	131.1	24.2	Vertical
C337	68	9,945	3,700	7,360	131.1	28.8	Vertical
C345	84	10,610	4,500	9,188	131.6	29.4	Vertical
C362	114	16,100	6,200	12,907	140.2	40	Vertical

JCB

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Bucket Breakout Force (lbs.)	Arm Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	High Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
215T	74	9,098	2,105	5,913	4,129	119	18.5	29.3	V
270T	74	11,003	2,795	6,543	5,807	125	23	31.7	V
300T	74	11,219	3,018	6,543	5,807	125	23.7	33	V
2TS-7T	74	10,232	1,014-2,096	6,288	1,907-3,181	122-142	18.5	29.3	R
3TS-8T	74	12,615	1,614-3,695	6,329	2,798-4,661	125-159	23.7	33	R

JOHN DEERE

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
317G	61	8,423	2,125	6,000	121	17	V
325G	70	9,500	2,590	8,750	126.1	21	V
331 P-Tier	95	11,914	3,150	11,000	132	25	V
333 P-Tier	106	12,183	3,850	13,750	132	25	V
335 P-Tier	115	12,300 / 13,542 with SG96 Dozer Blade	4,025	13,800	132	25	V

ASV

COMPACT TRACK LOADER

Model No.	Engine (gross hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
RT-25	24.7	3,755	665	2,240	101	11.3	R
RT-40	38.2	4,005	931	2,480	101	13.3	R
RT-50	53.8	5,180	1,400	2,920	109.6	13.3	R
RT-65 MAX-Series	67	7,480	1,925	4,800	116.5	22.2	R
VT-70 High Output MAX-Series	74.3	8,035	2,328	4,950	126.5	22.9	V
RT-75 MAX-Series	74	9,060	2,750	5,800	125.5	22.6	R
RT-75 Heavy Duty MAX-Series	74	9,210	2,800	5,800	125.5	22.6	R
VT-100 MAX-Series	103.5	10,345	3,500	8,500	132	41	V
VT-100 Forestry MAX-Series	103.5	11,570	4,100	8,500	132	41	V
RT-135 MAX-Series	132	12,075	3,500	6,720	125	50	R
RT-135 Forestry MAX-Series	132	12,990	4,150	6,720	125	50	R

*Bucket breakout force with foundry bucket

MANITOU

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
1050RT	34	4,720	1,499	109	14.5	R
1350RT	46	6,510	1,929	110	16.8	R
1650RT	69	8,020	2,357	120	13.65	R
1950RT	68.4	8,150	2,787	120	19	R
2100VT	69.3	8,865	3,000	121	22.8	V
2300VT	72	9,250	3,286	121	22.8	V
2750VT	72	10,051	3,929	129.5	26	V

*Bucket breakout force not provided

CATERPILLAR

COMPACT TRACK LOADER

Model No.	Engine (net hp)	Operating Weight (lbs.)	Rated Operating Capacity (lbs.)	Breakout Force [Tilt] (lbs.)	Height to Hinge Pin (in.)	Std. Hydraulic Flow (gpm)	Vertical (V) or Radial (R) Lift
239D3	66	7,434	1,530	3,913	111.2	18	R
249D3	66	7,831	1,740	3,907	118.2	18	V
259D3	73	8,987	2,010	4,965	121	20	V
255	74	9,578	2,499	6,746	124	23	V
279D3	73	10,095	2,220	7,285	124.9	23	R
289D3	73	10,688	2,890	7,291	125.1	23	V
265	74	10,492	2823	8,680	132	23	V
299D3	95	11,464	3,480	7,270	126.3	23	V
299D3 XE	106	11,756	3,560	7,270	126.3	23	V
299D3 XE Land Management	106	12,764	4,340	7,270	126.3	23	V