

ZERO-TURN MOWER spec guide

There is no shortage of options to consider when it comes to purchasing a new zero-turn mower. What kind of power and speed do you need? What kind of applications are you targeting with this piece of equipment? What type of mower best meets the needs of that application? The questions can become quite overwhelming.

That is why *Green Industry Pros* is making it easier for you by providing a side-by-side analysis of the specifications you need to make a solid purchasing decision. Here you can find a guide to the models available from a variety of zero-turn manufacturers. While we couldn't list every zero-turn available on the market here, you can find a more comprehensive interactive online guide at www.greenindustrypros.com/specguide. Check out Through the Grapevine on Page 4 for more details and happy hunting!



The Cub Cadet PRO Z 972 SD zero-turn allows you to comfortably mow a straight line, execute zero-degree turns and operate on a hillside with up to a 25-degree slope.

Cub Cadet

MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	OVERALL DIMENSIONS & WEIGHT	APPROXIMATE BLADE SPEED	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
Pro Z 160 S EFI	1 to 5 inches	9.5 MPH	60 inches	80 inches (L) by 62 inches (W) by 48 inches (H) and 1,000 pounds	18,500 FPM	7 gallons of gasoline	Kohler Confidant EFI	Fully welded 12-gauge channel frame with 14-gauge steel reinforcements	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
Pro Z 160 L EFI	1 to 5 inches	9.5 MPH	60 inches	80 inches (L) by 62 inches (W) by 48 inches (H) and 1,030 pounds	18,500 FPM	7 gallons of gasoline	Kohler Confidant EFI	Fully welded 12-gauge channel frame with 14-gauge steel reinforcements	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
Pro Z 160 L KW	1 to 5 inches	9.5 MPH	60 inches	80 inches (L) by 62 inches (W) by 48 inches (H) and 1,030 pounds	18,500 FPM	7 gallons of gasoline	Kawasaki FX730V	Fully welded 12-gauge channel frame with 14-gauge steel reinforcements	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
Pro Z 560 S KW	1 to 5 inches	10 MPH	60 inches	84 inches (L) by 56 inches (W) by 50 inches (H) and 1,424 pounds	18,500 FPM	14.9 gallons of gasoline	Kawasaki FX850V	3/8- by 5-inch full-length steel rail frame with 2- by 3-inch front axle and 3- by 5-inch hub	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
Pro Z 560 L KW	1 to 5 inches	10 MPH	60 inches	84 inches (L) by 62 inches (W) by 50 inches (H) and 1,324 pounds	18,500 FPM	14.9 gallons of gasoline	Kawasaki FX850V	3/8- by 5-inch full-length steel rail frame with 2- by 3-inch front axle and 3- by 5-inch hub	Front: 13 by 6.5 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
Pro Z 760 S KW	1 to 5 inches	12 MPH	60 inches	86 inches (L) by 62 inches (W) by 52 inches (H) and 1,562 pounds	18,500 FPM	14.9 gallons of gasoline	Kawasaki FX921V	3/8- by 5-inch full-length steel rail frame with 2- by 3-inch front axle and 3- by 5-inch hub	Front: 16 by 6.5 inches - 8 inches; Rear: 24 by 12 inches - 12 inches
Pro Z 760 L KW	1 to 5 inches	12 MPH	60 inches	86 inches (L) by 62 inches (W) by 52 inches (H) and 1,424 pounds	18,500 FPM	14.9 gallons of gasoline	Kawasaki FX921V	3/8- by 5-inch full-length steel rail frame with 2- by 3-inch front axle and 3- by 5-inch hub	Front: 13 by 6.5 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
Pro Z 760 S KW	1 to 5 inches	12 MPH	60 inches	86 inches (L) by 62 inches (W) by 52 inches (H) and 1,424 pounds	18,500 FPM	14.9 gallons of gasoline	Kawasaki FX850V EFI	3/8- by 5-inch full-length steel rail frame with 2- by 3-inch front axle and 3- by 5-inch hub	Front: 16 by 6.5 inches - 8 inches; Rear: 24 by 12 inches - 12 inches
Pro Z 972 SD	1 to 5 inches	12 MPH	72 inches	88 inches (L) by 85 inches (W) by 49 inches (H) and 1,850 pounds	18,500 FPM	14.9 gallons of gasoline	Kawasaki FX1000V	3/8- by 5-inch full-length steel rail frame with 2- by 3-inch front axle and 3- by 5-inch hub	Front: 16 by 6.5 inches - 8 inches; Rear: 25 by 9 inches - 12 inches
Pro Z 972 L KW	1 to 5 inches	14 MPH	72 inches	88 inches (L) by 74 inches (W) by 52 inches (H) and 1,591 pounds	18,500 FPM	14.9 gallons of gasoline	Kawasaki FX1000V	3/8- by 5-inch full-length steel rail frame with 2- by 3-inch front axle and 3- by 5-inch hub	Front: 15 by 6 inches - 6 inches; Rear: 26 by 12 inches - 12 inches

Ferris

The Ferris ISX 800 zero-turn comes equipped with a patent-pending ForeFront suspension system to offer more controlled motion, which results in a smoother ride, precise tracing of the terrain and an improved cut.



MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS & WEIGHT	APPROXIMATE BLADE SPEED	FUEL CAPACITY	ENGINE	TIRES
IS 3200	1.5 to 5 inches	12 MPH forward; 5 MPH reverse	61 or 72 inches	Zero-turn	61-inch deck: 84.5 inches (L) by 66.5 to 77 inches (W) and 1,470 pounds 72-inch deck: 84.5 inches (L) by 74 to 86 inches (W) and 1,579 pounds	17,600 to 18,500 FPM	11 gallons of gasoline	Vanguard BIG BLOCK with Oil Guard, 32 HP; Kawasaki FX1000V, 35 HP; or Vanguard BIG BLOCK EFI with Oil Guard, 37 HP	Front: 13 by 6.5 inches - 6 inches; Rear: 26 by 12 inches - 12 inches
IS 2600	1.75 to 5 inches	10 MPH forward; 6 MPH reverse	61 inches	Zero-turn	86.25 inches (L) by 63.5 to 76.75 inches (W) and 1,606 pounds	17,600 to 18,500 FPM	11 gallons of diesel	Yanmar diesel	Front: 13 by 6.5 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
IS 2100	1.5 to 5 inches	10 MPH forward; 5 MPH reverse	52 or 61 inches	Zero-turn	52-inch deck: 82.5 inches (L) by 57 to 67 inches (W) and 1,223 pounds 61-inch deck: 82.5 inches (L) by 61.5 to 78 inches (W) and 1,295 pounds	17,600 to 18,500 FPM	11 gallons of gasoline	Kawasaki FX801V, 25.5 HP; Vanguard 810, 26 HP; Vanguard 810 EFI with Oil Guard, 28 HP; or Kawasaki FX850V EFI, 29.5 HP	Front: 13 by 5 inches - 6 inches (52- and 61-inch deck) Rear: 24 by 9.5 inches - 12 inches (52-inch deck) Rear: 24 by 12 inches - 12 inches (61-inch deck)
ISX 800	1.5 to 5 inches	10 MPH forward; 5 MPH reverse	52 or 61 inches	Zero-turn	52-inch deck: 81 inches (L) by 57 to 65 inches (W) and 1,119 pounds 61-inch deck: 83 inches (L) by 63.5 to 75 inches (W) and 1,197 pounds	17,600 to 18,500 FPM	5.5 gallons of gasoline	Kawasaki FS730V, 24 HP; Briggs & Stratton Commercial Series, 27 HP; Briggs & Stratton Commercial Series EFI, 27 HP; Vanguard 810, 26 HP; or Kawasaki FT730V EFI, 26 HP	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
IS 700	1.5 to 5 inches	10 MPH forward; 5 MPH reverse	52 or 61 inches	Zero-turn	52-inch deck: 81 inches (L) by 56.5 to 66.75 inches (W) and 1,059 pounds 61-inch deck: 81 inches (L) by 65.5 to 75.75 inches (W) and 1,113 pounds	17,600 to 18,500 FPM	5.5 gallons of gasoline	Briggs & Stratton Commercial Series, 27 HP	Front: 13 by 5 inches - 6 inches; Rear: 22 by 11 inches - 10 inches
IS 600	1.5 to 4.5 inches	10 MPH forward; 5 MPH reverse	44, 48 or 52 inches	Zero-turn	44-inch deck: 80 inches (L) by 47 to 59 inches (W) and 920 pounds 48-inch deck: 80 inches (L) by 51 to 63 inches (W) and 942 pounds 52-inch deck: 80 inches (L) by 56.5 to 66.75 inches (W) and 964 pounds	17,600 to 18,500 FPM	5.5 gallons of gasoline	Briggs & Stratton Commercial Series, 25 HP; Kawasaki FS600V, 18.5 HP; or Kawasaki FS691V, 23 HP	Front: 11 by 4 inches - 5 inches (44-inch deck) Rear: 20 by 8 inches - 10 inches (44-inch deck) Front: 13 by 5 inches - 6 inches (48- and 52-inch deck) Rear: 22 by 11 inches - 10 inches (48- and 52-inch deck)
400S	1.5 to 5 inches	8 MPH forward; 4 MPH reverse	44 or 48 inches	Zero-turn	44-inch deck: 73.5 inches (L) by 56 inches (W) and 728 pounds 48-inch deck: 73.5 inches (L) by 53 to 59 inches (W) and 753 pounds	17,600 to 18,500 FPM	5.5 gallons of gasoline	Kawasaki FR651V, 22 HP; Briggs & Stratton Commercial Series, 23 HP; Kawasaki FR651V, 21.5 HP; or Briggs & Stratton Commercial Series, 25 HP	Front: 11 by 4 inches - 5 inches; Rear: 20 by 10 inches - 10 inches
F320	1.5 to 5 inches	12 MPH forward; 6 MPH reverse	61 or 72 inches	Zero-turn	61-inch deck: 81 inches (L) by 63 to 76 inches (W) and 1,400 pounds 72-inch deck: 83.5 inches (L) by 74 to 87.5 inches (W) and 1,439 pounds	17,600 to 18,500 FPM	11 gallons of gasoline	Kawasaki FX850V EFI, 29.5 HP; Vanguard BIG BLOCK with Oil Guard, 32 HP; or Vanguard BIG BLOCK EFI with Oil Guard, 37 HP	Front: 13 by 6.5 inches - 6 inches; Rear: 26 by 12 inches - 12 inches
F210	1.5 to 5 inches	10 MPH forward; 5 MPH reverse	61 inches	Zero-turn	80 inches (L) by 63 to 76 inches (W) and 1,190 pounds	17,600 to 18,500 FPM	11 gallons of gasoline	Kawasaki FX801V, 25.5 HP; Vanguard 810, 26 HP; or Vanguard 810 EFI with Oil Guard, 28 HP	Front: 13 by 6.5 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
F160	1.5 to 5 inches	10 MPH forward; 5 MPH reverse	48 or 52 inches	Zero-turn	48-inch deck: 78 inches (L) by 51 to 61.5 inches (W) and 1,116 pounds 52-inch deck: 78 inches (L) by 54 to 67 inches (W) and 1,145 pounds	17,600 to 18,500 FPM	11 gallons of gasoline	Kawasaki FX730V, 23.5 HP; Vanguard 810, 26 HP; or Vanguard 810 EFI, 28 HP	Front: 13 by 6.5 inches - 6 inches; Rear: 24 by 9.5 inches - 12 inches
F60	1.5 to 4.5 inches	7 MPH forward; 4 MPH reverse	36 inches	Zero-turn	73.75 inches (L) by 40.5 to 49.5 inches (W) and 732 pounds	17,600 to 18,500 FPM	8 gallons of gasoline	Kawasaki FX600V, 19 HP; or Briggs & Stratton Commercial Series, 25 HP	Front: 11 by 4 inches - 5 inches; Rear: 20 by 7 inches - 10 inches
SRS Z3X	1.75 to 5 inches	12 MPH forward; 5 MPH reverse	52, 61 or 72 inches	Stand-on zero-turn	52-inch deck: 69 inches (L) by 54.5 to 65 inches (W) and 1,184 pounds 61-inch deck: 73.75 inches (L) by 67 to 75.25 inches (W) and 1,267 pounds 72-inch deck: 74.5 inches (L) by 77 to 85.25 inches (W) and 1,327 pounds	17,600 to 18,500 FPM	11 gallons of gasoline	Vanguard BIG BLOCK EFI with Oil Guard, 33 HP; Vanguard BIG BLOCK EFI with Oil Guard, 37 HP; or Kawasaki FX850V EFI, 29.5 HP	Front: 13 by 6.5 inches - 6 inches (52-, 61- or 72-inch deck) Rear: 24 by 9.5 inches - 12 inches (52-inch deck) Rear: 24 by 12 inches - 12 inches (61- or 72-inch deck)
SRS Z2	1.75 to 5 inches	10 MPH forward; 5 MPH reverse	52 or 61 inches	Stand-on zero-turn	52-inch deck: 67 inches (L) by 54.75 to 65 inches (W) and 938 pounds 61-inch deck: 72.75 inches (L) by 64 to 77 inches (W) and 998 pounds	17,600 to 18,500 FPM	8 gallons of gasoline	Kawasaki FX801V, 25.5 HP; Kawasaki FX730V EFI, 25.5 HP; or Vanguard 810 EFI with Oil Guard, 28 HP	Front: 13 by 5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
SRS Z1	1.75 to 4.5 inches	8 MPH forward; 4 MPH reverse	36 or 48 inches	Stand-on zero-turn	36-inch deck: 63.75 inches (L) by 42 to 49 inches (W) and 813 pounds 48-inch deck: 65 inches (L) by 54 to 59.5 inches (W) and 866 pounds	17,600 to 18,500 FPM	6 gallons of gasoline	Kawasaki FX600V, 19 HP; Vanguard, 23 HP; Kawasaki FX691V, 22 HP; or Vanguard, 23 HP	Front: 11 by 4 inches - 5 inches (36- or 48-inch deck) Rear: 23 by 8.5 inches - 12 inches (36-inch deck) Rear: 23 by 10.5 inches - 12 inches (48-inch deck)

Exmark Manufacturing

MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS & WEIGHT	APPROXIMATE BLADE SPEED	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
Lazer Z Diesel - LZS80TDYM604WO	1 to 5.5 inches	11 MPH forward; 6 MPH reverse	60-inch side discharge	Mid-mount zero-turn	96.3 inches (L) by 72.8 inches (W) by 72.5 inches (H) and 1,915 pounds	18,500 FPM	12 gallons of diesel	Yanmar 3TNV80FT	Welded tubular steel unibody	Front: 15 by 6 inches - 6 inches; Rear: 26 by 12 inches - 12 inches
Lazer Z Diesel - LZS80TDYM724WO	1 to 5.5 inches	11 MPH forward; 6 MPH reverse	72-inch side discharge	Mid-mount zero-turn	99.6 inches (L) by 84.9 inches (W) by 72.5 inches (H) and 1,930 pounds	18,500 FPM	12 gallons of diesel	Yanmar 3TNV80FT	Welded tubular steel unibody	Front: 15 by 6 inches - 6 inches; Rear: 26 by 12 inches - 12 inches
Lazer Z Diesel - LZS80TDYM72RWO	1 to 5.5 inches	11 MPH forward; 6 MPH reverse	72-inch rear discharge	Mid-mount zero-turn	100.6 inches (L) by 78 inches (W) by 72.5 inches (H) and 2,041 pounds	18,500 FPM	12 gallons of diesel	Yanmar 3TNV80FT	Welded tubular steel unibody	Front: 15 by 6 inches - 6 inches; Rear: 26 by 12 inches - 12 inches
Lazer Z Diesel - LZS88CDYM604WO	1 to 5.5 inches	12.5 MPH forward; 7 MPH reverse	60-inch side discharge	Mid-mount zero-turn	96.3 inches (L) by 72.8 inches (W) by 72.5 inches (H) and 2,124 pounds	18,500 FPM	12 gallons of diesel	Yanmar 3TNV88C	Welded tubular steel unibody	Front: 15 by 6 inches - 6 inches; Rear: 26 by 12 inches - 12 inches
Lazer Z Diesel - LZS88CDYM724WO	1 to 5.5 inches	12.5 MPH forward; 7 MPH reverse	72-inch side discharge	Mid-mount zero-turn	99.6 inches (L) by 84.9 inches (W) by 72.5 inches (H) and 2,133 pounds	18,500 FPM	12 gallons of diesel	Yanmar 3TNV88C	Welded tubular steel unibody	Front: 15 by 6 inches - 6 inches; Rear: 26 by 12 inches - 12 inches
Lazer Z Diesel - LZS88CDYM96RWO	1 to 5.5 inches	12.5 MPH forward; 7 MPH reverse	96-inch rear discharge	Mid-mount zero-turn	97.3 inches (L) by 101.2 inches (W) by 72.5 inches (H) and 2,584 pounds	18,500 FPM	12 gallons of diesel	Yanmar 3TNV88C	Welded tubular steel unibody	Front: 15 by 6 inches - 6 inches; Rear: 26 by 12 inches - 12 inches
Navigator - NVS730AK48000	1 to 4 inches	7 MPH forward; 4.5 MPH reverse	48-inch center discharge	Front-mount zero-turn	94.5 inches (L) by 49.2 inches (W) by 51.2 inches (H) and 1,170 pounds	18,500 FPM	7.5 gallons of gasoline	Kohler ECH730 EFI	Welded tubular steel	Front: 8 by 3 inches - 4 inches; Rear: 18 by 10.5 inches - 10 inches
Navigator - NVS740CK42000	1 to 4 inches	7 MPH forward; 4.5 MPH reverse	42-inch center discharge	Front-mount zero-turn	91.8 inches (L) by 43.2 inches (W) by 51.2 inches (H) and 1,140 pounds	18,500 FPM	7.5 gallons of gasoline	Kohler CH740	Welded tubular steel	Front: 8 by 3 inches - 4 inches; Rear: 18 by 10.5 inches - 10 inches
Radius E-Series - RAE702GEM44300	1.5 to 5 inches	8 MPH forward; 5 MPH reverse	44-inch side discharge	Mid-mount zero-turn	81.7 inches (L) by 45.4 inches (W) by 69.7 inches (H) and 798 pounds	18,500 FPM	7 gallons of gasoline	Exmark 708	Welded tubular steel unibody	Front: 13 by 5 inches - 6 inches; Rear: 22 by 8.5 inches - 12 inches
Radius E-Series - RAE708GEM48300	1.5 to 5 inches	8 MPH forward; 5 MPH reverse	48-inch side discharge	Mid-mount zero-turn	81.7 inches (L) by 59.5 inches (W) by 69.7 inches (H) and 849 pounds	18,500 FPM	7 gallons of gasoline	Exmark 708	Welded tubular steel unibody	Front: 13 by 6.5 inches - 6 inches; Rear: 22 by 9.5 inches - 12 inches
Radius E-Series - RAE708GEM52300	1.5 to 5 inches	8 MPH forward; 5 MPH reverse	52-inch side discharge	Mid-mount zero-turn	81.7 inches (L) by 64.3 inches (W) by 69.7 inches (H) and 862 pounds	18,500 FPM	7 gallons of gasoline	Exmark 708	Welded tubular steel unibody	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 9.5 inches - 12 inches
Radius E-Series - RAE708GEM60300	1.5 to 5 inches	8 MPH forward; 5 MPH reverse	60-inch side discharge	Mid-mount zero-turn	82.2 inches (L) by 72.3 inches (W) by 69.7 inches (H) and 901 pounds	18,500 FPM	7 gallons of gasoline	Exmark 708	Welded tubular steel unibody	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
Radius S-Series - RAS708GEM483C3	1.5 to 5 inches	9 MPH forward; 5 MPH reverse	48-inch side discharge	Mid-mount zero-turn	81.7 inches (L) by 59.5 inches (W) by 69.7 inches (H)	18,500 FPM	7 gallons of gasoline	Exmark 708	Welded tubular steel unibody	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 9.5 inches - 12 inches
Radius S-Series - RAS708GEM523C3	1.5 to 5 inches	9 MPH forward; 5 MPH reverse	52-inch side discharge	Mid-mount zero-turn	81.7 inches (L) by 64.3 inches (W) by 70.2 inches (H)	18,500 FPM	7 gallons of gasoline	Exmark 708	Welded tubular steel unibody	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 9.5 inches - 12 inches
Radius S-Series - RAS708GEM603C3	1.5 to 5 inches	9 MPH forward; 5 MPH reverse	60-inch side discharge	Mid-mount zero-turn	82.2 inches (L) by 72.3 inches (W) by 70.2 inches (H)	18,500 FPM	7 gallons of gasoline	Exmark 708	Welded tubular steel unibody	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
Radius S-Series - RAS708GEM60RC3	1.5 to 5 inches	9 MPH forward; 5 MPH reverse	60-inch rear discharge	Mid-mount zero-turn	84.3 inches (L) by 66 inches (W) by 70.2 inches (H)	18,500 FPM	7 gallons of gasoline	Exmark 708	Welded tubular steel unibody	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
Radius X-Series - RAX651GKA484A3	1.5 to 5 inches	10 MPH forward; 6 MPH reverse	48-inch side discharge	Mid-mount zero-turn	81.7 inches (L) by 59.5 inches (W) by 70.4 inches (H) and 937 pounds	18,500 FPM	7 gallons of gasoline	Kawasaki FX651V	Welded tubular steel unibody	Front: 13 by 6.5 inches - 6 inches; Rear: 24 by 9.5 inches - 12 inches
Radius X-Series - RAX691GKA524A3	1.5 to 5 inches	10 MPH forward; 6 MPH reverse	52-inch side discharge	Mid-mount zero-turn	81.7 inches (L) by 64.6 inches (W) by 70.4 inches (H) and 957 pounds	18,500 FPM	7 gallons of gasoline	Kawasaki FX691V	Welded tubular steel unibody	Front: 13 by 6.5 inches - 6 inches; Rear: 24 by 9.5 inches - 12 inches
Radius X-Series - RAX730GKA604A3	1.5 to 5 inches	10 MPH forward; 6 MPH reverse	60-inch side discharge	Mid-mount zero-turn	82.2 inches (L) by 72.7 inches (W) by 70.4 inches (H) and 1,006 pounds	18,500 FPM	7 gallons of gasoline	Kawasaki FX730V	Welded tubular steel unibody	Front: 13 by 6.5 inches - 6 inches; Rear: 24 by 10.5 inches - 12 inches

The all-new 2019 Exmark Staris stand-on zero-turn mower delivers commercial durability, ergonomics and ease of service to maximize productivity and profitability for landscape contractors.



MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS & WEIGHT	APPROXIMATE BLADE SPEED	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
Staris E-Series - STE600CKA32300	1 to 5 inches	7.5 MPH forward; 4 MPH reverse	32-inch side discharge	Stand-on zero-turn	58.1 inches (L) by 47.3 inches (H) and 712 pounds	18,500 FPM	5 gallons of gasoline	Kawasaki FS600V	Welded tubular steel	Front: 9 by 4.5 inches - 5 inches; Rear: 21 by 8.5 inches - 10 inches
Staris E-Series - STE600CKA36300	1 to 5 inches	7.5 MPH forward; 4 MPH reverse	36-inch side discharge	Stand-on zero-turn	58.1 inches (L) by 47.1 inches (H) and 720 pounds	18,500 FPM	5 gallons of gasoline	Kawasaki FS600V	Welded tubular steel	Front: 9 by 4.5 inches - 5 inches; Rear: 21 by 8.5 inches - 10 inches
Staris E-Series - STE600GKA44300	1 to 5 inches	7.5 MPH forward; 4 MPH reverse	44-inch side discharge	Stand-on zero-turn	61.7 inches (L) by 47.1 inch (H) and 737 pounds	18,500 FPM	5 gallons of gasoline	Kawasaki FS600V	Welded tubular steel	Front: 9 by 4.5 inches - 5 inches; Rear: 21 by 8.5 inches - 10 inches
Staris S-Series - STS651GKA48400	1.5 to 5 inches	10 MPH forward; 4 MPH reverse	48-inch side discharge	Stand-on zero-turn	69.3 inches (L) by 59.6 inches (W) by 46.7 inches (H) and 960 pounds	18,500 FPM	10 gallons of gasoline	Kawasaki FX651V	Welded tubular steel	Front: 12 by 6 inches - 6 inches; Rear: 23 by 8.5 inches - 12 inches
Staris S-Series - STS730AKC52400	1.5 to 5 inches	10 MPH forward; 4 MPH reverse	52-inch side discharge	Stand-on zero-turn	69.3 inches (L) by 64.8 inches (W) by 46.7 inches (H) and 990 pounds	18,500 FPM	10 gallons of gasoline	Kohler ECV730 EFI	Welded tubular steel	Front: 12 by 6 inches - 6 inches; Rear: 23 by 9.5 inches - 12 inches
Staris S-Series - STS730GKA52400	1.5 to 5 inches	10 MPH forward; 4 MPH reverse	52-inch side discharge	Stand-on zero-turn	69.3 inches (L) by 64.8 inches (W) by 46.7 inches (H) and 990 pounds	18,500 FPM	10 gallons of gasoline	Kawasaki FX730V	Welded tubular steel	Front: 12 by 6 inches - 6 inches; Rear: 23 by 9.5 inches - 12 inches
Staris S-Series - STS730GKA60400	1.5 to 5 inches	10 MPH forward; 4 MPH reverse	60-inch side discharge	Stand-on zero-turn	70.5 inches (L) by 72.8 inches (W) by 46.7 inches (H) and 1,045 pounds	18,500 FPM	10 gallons of gasoline	Kawasaki FX730V	Welded tubular steel	Front: 12 by 6 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
Staris S-Series - STS740CKA60400	1.5 to 5 inches	10 MPH forward; 4 MPH reverse	60-inch side discharge	Stand-on zero-turn	70.5 inches (L) by 72.8 inches (W) by 46.7 inches (H) and 1,045 pounds	18,500 FPM	10 gallons of gasoline	Kohler ECV740 EFI	Welded tubular steel	Front: 12 by 6 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches



The Z-MAX is our largest and most productive sprayer. It is large enough to handle commercial sites, but nimble enough for residential properties. The zero-turn maneuverability makes it simple to navigate the tightest and most challenging areas. Z-Spray is committed to delivering performance and excellence in all our products, parts and service.



z-spray.com

Visit www.greenindustrypros.com/10155867

The Grasshopper Company

The diesel-powered Grasshopper 900D FrontMount zero-turn delivers more torque to power through heavy grass at faster mowing speeds, while reducing operating costs by using 60 percent less fuel than same-sized gasoline engines.



MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS & WEIGHT*	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
325D-52	1 to 5 inches	10 MPH	52 inches	Mid-mount zero-turn	53.5 inches (W) by 82.5 inches (L) and 1,310 pounds	12 gallons of diesel	Kubota MaxTorque diesel, 898cc	Steel	23 by 10.5 inches - 12 inches
325D-61	1 to 5 inches	10.5 MPH	61 inches	Mid-mount zero-turn	62.5 inches (W) by 84 inches (L) and 1,360 pounds	12 gallons of diesel	Kubota MaxTorque diesel, 898cc	Steel	24 by 12 inches - 12 inches
325D-72	1 to 5 inches	10.5 MPH	72 inches	Mid-mount zero-turn	73.5 inches (W) by 87.5 inches (L) and 1,450 pounds	12 gallons of diesel	Kubota MaxTorque diesel, 898cc	Steel	24 by 12 inches - 12 inches
400D-61	1 to 5 inches	11 MPH	61 inches	Mid-mount zero-turn	62.5 inches (W) by 86 inches (L) and 1,450 pounds	12 gallons of diesel	Kubota MaxTorque diesel, 1.3L	Steel	24 by 12 inches - 12 inches
400D-72	1 to 5 inches	11 MPH	72 inches	Mid-mount zero-turn	73.5 inches (W) by 89.5 inches (L) and 1,540 pounds	12 gallons of diesel	Kubota MaxTorque diesel, 1.3L	Steel	24 by 12 inches - 12 inches
432-61	1 to 5 inches	11 MPH	61 inches	Mid-mount zero-turn	62.5 inches (W) by 86 inches (L) and 1,410 pounds	12 gallons of gasoline	Kubota, 962cc	Steel	24 by 12 inches - 12 inches
432-72	1 to 5 inches	11 MPH	72 inches	Mid-mount zero-turn	73.5 inches (W) by 89.5 inches (L) and 1,500 pounds	12 gallons of gasoline	Kubota, 962cc	Steel	24 by 12 inches - 12 inches
524V-42	2 to 4.5 inches	8 MPH	42 inches	Front-mount zero-turn	43.5 inches (W) by 98 inches (L) and 935 pounds	4 gallons of gasoline	Briggs & Stratton Commercial Turf, 724cc	Steel	20 by 8 inches - 10 inches
526V-52	2 to 4.5 inches	8 MPH	52 inches	Front-mount zero-turn	53.5 inches (W) by 102 inches (L) and 1,025 pounds	4 gallons of gasoline	Briggs & Stratton Vanguard, 810cc	Steel	20 by 8 inches - 10 inches
623T with 48-inch deck	1.25 to 5 inches	8.5 MPH	48 inches	Front-mount zero-turn	49.5 inches (W) by 100 inches (L) and 1,040 pounds	7.2 gallons of gasoline	Kohler Command Pro, 694cc	Steel	22 by 10 inches - 8 inches
623T with 52-inch deck	1.25 to 5 inches	8.5 MPH	52 inches	Front-mount zero-turn	53.5 inches (W) by 101 inches (L) and 1,120 pounds	7.2 gallons of gasoline	Kohler Command Pro, 694cc	Steel	22 by 10 inches - 8 inches
725KT with 52-inch deck	1.25 to 5 inches	9 MPH	52 inches	Front-mount zero-turn	53.5 inches (W) by 105.5 inches (L) and 1,260 pounds	7.2 gallons of gasoline	Kohler Command Pro, 747cc	Steel	22 by 11 inches - 10 inches
725KT with 61-inch deck	1.25 to 5 inches	9 MPH	61 inches	Front-mount zero-turn	62.5 inches (W) by 107.5 inches (L) and 1,310 pounds	7.2 gallons of gasoline	Kohler Command Pro, 747cc	Steel	22 by 11 inches - 10 inches
727T EFI with 52-inch deck	1.25 to 5 inches	10 MPH	52 inches	Front-mount zero-turn	53.5 inches (W) by 105.5 inches (L) and 1,285 pounds	7.2 gallons of gasoline	Kohler Command Pro EFI, 747cc	Steel	22 by 11 inches - 10 inches
727T EFI with 61-inch deck	1.25 to 5 inches	10 MPH	61 inches	Front-mount zero-turn	62.5 inches (W) by 107.5 inches (L) and 1,335 pounds	7.2 gallons of gasoline	Kohler Command Pro EFI, 747cc	Steel	22 by 11 inches - 10 inches
727T EFI with 72-inch deck	1.25 to 5 inches	10 MPH	61 inches	Front-mount zero-turn	73.5 inches (W) by 117.5 inches (L) and 1,460 pounds	7.2 gallons of gasoline	Kohler Command Pro EFI, 747cc	Steel	22 by 11 inches - 10 inches
729BT6 with 52-inch deck	1.25 to 5 inches	10 MPH	52 inches	Front-mount zero-turn	53.5 inches (W) by 105.5 inches (L) and 1,300 pounds	7.2 gallons of gasoline	Briggs & Stratton Vanguard Big Block, 895cc	Steel	22 by 11 inches - 10 inches
729BT6 with 61-inch deck	1.25 to 5 inches	10 MPH	61 inches	Front-mount zero-turn	62.5 inches (W) by 107.5 inches (L) and 1,350 pounds	7.2 gallons of gasoline	Briggs & Stratton Vanguard Big Block, 895cc	Steel	22 by 11 inches - 10 inches
729BT6 with 72-inch deck	1.25 to 5 inches	10 MPH	72 inches	Front-mount zero-turn	73.5 inches (W) by 117.5 inches (L) and 1,475 pounds	7.2 gallons of gasoline	Briggs & Stratton Vanguard Big Block, 895cc	Steel	22 by 11 inches - 10 inches
735BT6 with 61-inch deck	1.25 to 5 inches	10 MPH	61 inches	Front-mount zero-turn	62.5 inches (W) by 107.5 inches (L) and 1,350 pounds	7.2 gallons of gasoline	Briggs & Stratton Vanguard Big Block, 993cc	Steel	22 by 11 inches - 10 inches
735BT6 with 72-inch deck	1.25 to 5 inches	10 MPH	72 inches	Front-mount zero-turn	73.5 inches (W) by 117.5 inches (L) and 1,475 pounds	7.2 gallons of gasoline	Briggs & Stratton Vanguard Big Block, 993cc	Steel	22 by 11 inches - 10 inches
721DT with 52-inch deck	1.25 to 5 inches	9 MPH	52 inches	Front-mount zero-turn	53.5 inches (W) by 105.5 inches (L) and 1,335 pounds	8 gallons of diesel	Kubota MaxTorque diesel, 719cc	Steel	22 by 11 inches - 10 inches
725DT6 with 52-inch deck	1.25 to 5 inches	10 MPH	52 inches	Front-mount zero-turn	53.5 inches (W) by 105.5 inches (L) and 1,370 pounds	8 gallons of diesel	Kubota MaxTorque diesel, 898cc	Steel	22 by 11 inches - 10 inches
725DT6 with 61-inch deck	1.25 to 5 inches	10 MPH	61 inches	Front-mount zero-turn	62.5 inches (W) by 107.5 inches (L) and 1,420 pounds	8 gallons of diesel	Kubota MaxTorque diesel, 898cc	Steel	22 by 11 inches - 10 inches
725DT6 with 72-inch deck	1.25 to 5 inches	10 MPH	72 inches	Front-mount zero-turn	73.5 inches (W) by 117.5 inches (L) and 1,545 pounds	8 gallons of diesel	Kubota MaxTorque diesel, 898cc	Steel	22 by 11 inches - 10 inches
729T6 with 52-inch deck	1.25 to 5 inches	10 MPH	52 inches	Front-mount zero-turn	53.5 inches (W) by 105.5 inches (L) and 1,370 pounds	7.2 gallons of gasoline	Kubota, 962cc	Steel	22 by 11 inches - 10 inches
729T6 with 61-inch deck	1.25 to 5 inches	10 MPH	61 inches	Front-mount zero-turn	62.5 inches (W) by 107.5 inches (L) and 1,420 pounds	7.2 gallons of gasoline	Kubota, 962cc	Steel	R22 by 11 inches - 10 inches
729T6 with 72-inch deck	1.25 to 5 inches	10 MPH	72 inches	Front-mount zero-turn	73.5 inches (W) by 117.5 inches (L) and 1,545 pounds	7.2 gallons of gasoline	Kubota, 962cc	Steel	22 by 11 inches - 10 inches
900D 1.3L with 61-inch deck	1.25 to 5 inches	11 MPH	61 inches	Front-mount zero-turn	62.5 inches (W) by 112.5 inches (L) and 1,570 pounds	8 gallons of diesel	Kubota MaxTorque diesel, 1.3L	Steel	24 by 12 inches - 12 inches
900D 1.3L with 72-inch deck	1.25 to 5 inches	11 MPH	72 inches	Front-mount zero-turn	73.5 inches (W) by 120.5 inches (L) and 1,695 pounds	8 gallons of diesel	Kubota MaxTorque diesel, 1.3L	Steel	24 by 12 inches - 12 inches
932 with 61-inch deck	1.25 to 5 inches	11 MPH	61 inches	Front-mount zero-turn	62.5 inches (W) by 112.5 inches (L) and 1,520 pounds	7.2 gallons of gasoline	Kubota, 962cc	Steel	22 by 11 inches - 10 inches
932 with 72-inch deck	1.25 to 5 inches	11 MPH	72 inches	Front-mount zero-turn	73.5 inches (W) by 120.5 inches (L) and 1,645 pounds	7.2 gallons of gasoline	Kubota, 962cc	Steel	22 by 11 inches - 10 inches

*Mulching width is indicated; add 13.5 inches for a side-discharge chute.

INTRODUCING **STARIS**

BY **eXmark**



THE REVOLUTIONARY STAND-ON MOWER

Exmark® engineers reinvented the stand-on zero-turn mower from the ground up. The all-new Staris® delivers the commercial performance, durability, ergonomics and ease of service that landscape professionals need to maximize productivity and profitability. The Staris is available with 32- to 60-inch UltraCut™ cutting decks and Kohler® EFI and Kawasaki® V-Twin engine options.

E- and S-Series available Spring 2019

exmark.com    



AUGMENTED REALITY EXPERIENCE

- 1 Download & Open Exmark AR App
- 2 Scan the Staris above
- 3 Explore



Download the FREE **EXMARK AR App** to see the Staris come to life with an augmented reality experience right in front of your eyes.

ASK YOUR DEALER ABOUT FLEET DISCOUNTS WITH THE PURCHASE OF TWO STARIS STAND-ON RIDERS
Visit www.greenindustrypros.com/10155791



Husqvarna Z500 Series zero-turn mowers provide a comfortable user experience, high ground speeds and optimal traction, adding up to exceptional mowing efficiency.

Husqvarna

MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	OVERALL DIMENSIONS & WEIGHT*	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES (INCHES)
Z500 Zero-Turn Series Z560X (967 66 97-01)	1 to 5 inches	12 MPH	60 inches	73 inches (H) by 76 inches (W) by 81 inches (L) and 1,398 pounds	12 gallons of gasoline	Kawasaki, 31 HP	7 gauge	24 by 12 inches - 12 inches
Z500 Zero-Turn Series Z572X (967 66 98-01)	1 to 5 inches	12 MPH	72 inches	73 inches (H) by 85 inches (W) by 81 inches (L) and 1,448 pounds	12 gallons of gasoline	Kawasaki, 31 HP	7 gauge	24 by 12 inches - 12 inches
Z500 Zero-Turn Series Z548 50 State CARB (967 92 97-01)	1 to 5 inches	11 MPH	48 inches	73 inches (H) by 63.5 inches (W) by 81 inches (L) and 1,147 pounds	12 gallons of gasoline	Yamaha, 26 HP	10 gauge	23 by 8.5 inches - 12 inches
Z500 Zero-Turn Series Z554 (967 92 98-01)	1 to 5 inches	11 MPH	54 inches	73 inches (H) by 67.5 inches (W) by 81 inches (L) and 1,215 pounds	12 gallons of gasoline	Yamaha, 26 HP	10 gauge	23 by 10.5 inches - 12 inches
Z500 Zero-Turn Series Z560 (967 92 99-01)	1 to 5 inches	12 MPH	60 inches	73 inches (H) by 76 inches (W) by 81 inches (L) and 1,172 pounds	12 gallons of gasoline	Yamaha, 27.5 HP	7 gauge	23 by 10.5 inches - 12 inches
Z500 Zero-Turn Series Z554X (967 93 00-01)	1 to 5 inches	12 MPH	54 inches	73 inches (H) by 67.5 inches (W) by 81 inches (L) and 1,322 pounds	12 gallons of gasoline	Yamaha, 27.5 HP	7 gauge	23 by 10.5 inches - 12 inches
Z500 Zero-Turn Series Z554X (967 93 01-01)	1 to 5 inches	12 MPH	54 inches	73 inches (H) by 67.5 inches (W) by 81 inches (L) and 1,322 pounds	12 gallons of gasoline	Yamaha, 29 HP	7 gauge	23 by 10.5 inches - 12 inches
Z500 Zero-Turn Series Z560X (967 93 02-01)	1 to 5 inches	12 MPH	60 inches	73 inches (H) by 76 inches (W) by 81 inches (L) and 1,398 pounds	12 gallons of gasoline	Yamaha, 27.5 HP	7 gauge	24 by 12 inches - 12 inches
Z500 Zero-Turn Series Z560X 50 State CARB (967 93 03-01)	1 to 5 inches	12 MPH	60 inches	73 inches (H) by 76 inches (W) by 81 inches (L) and 1,398 pounds	12 gallons of gasoline	Yamaha, 27.5 HP	7 gauge	24 by 12 inches - 12 inches
Z500 Zero-Turn Series Z560X (967 93 04-01)	1 to 5 inches	12 MPH	60 inches	73 inches (H) by 76 inches (W) by 81 inches (L) and 1,398 pounds	12 gallons of gasoline	Yamaha, 31 HP	7 gauge	24 by 12 inches - 12 inches
Z500 Zero-Turn Series Z572X (967 93 05-01)	1 to 5 inches	12 MPH	72 inches	73 inches (H) by 85 inches (W) by 81 inches (L) and 1,448 pounds	12 gallons of gasoline	Yamaha, 33 HP	7 gauge	24 by 12 inches - 12 inches
V500 Stand-On Series V548 (967 67 25-01)	1 to 5 inches	9 MPH	48 inches	48 inches (H) by 57 inches (L) and 1,164 pounds	7 gallons of gasoline	Kawasaki, 24.5 HP	7 gauge	20 by 10.5 inches - 8 inches
V500 Stand-On Series V554 (967 67 26-01)	1 to 5 inches	9 MPH	54 inches	48 inches (H) by 57 inches (L) and 1,176 pounds	7 gallons of gasoline	Kawasaki, 24.5 HP	7 gauge	20 by 10.5 inches - 8 inches
M-ZT Series 52 (967 17 70-05)	1.5 to 4.5 inches	10 MPH	52 inches	72 inches (H) by 67 inches (W) by 75.5 inches (L) and 760 pounds	5 gallons of gasoline	Briggs & Stratton, 26 HP	11 gauge	23 by 9.5 inches - 12 inches
M-ZT Series 52 (967 17 70-11)	1.5 to 4.5 inches	10 MPH	52 inches	72 inches (H) by 67 inches (W) by 75.5 inches (L) and 760 pounds	5 gallons of gasoline	Kawasaki, 22 HP	11 gauge	23 by 9.5 inches - 12 inches
M-ZT Series 52 (967 84 40-01)	1.5 to 4.5 inches	10 MPH	52 inches	72 inches (H) by 67 inches (W) by 75.5 inches (L) and 760 pounds	5 gallons of gasoline	Kohler, 23 HP	11 gauge	23 by 9.5 inches - 12 inches
M-ZT Series 61 (967 17 70-07)	1.5 to 4.5 inches	10 MPH	61 inches	61 inches (H) by 67 inches (W) by 76 inches (L) and 790 pounds	5 gallons of gasoline	Briggs & Stratton, 27 HP	11 gauge	23 by 10.5 inches - 12 inches
M-ZT Series 61 (967 84 42-01)	1.5 to 4.5 inches	10 MPH	61 inches	61 inches (H) by 67 inches (W) by 76 inches (L) and 790 pounds	5 gallons of gasoline	Kohler, 25 HP	11 gauge	23 by 10.5 inches - 12 inches
M-ZT Series 61 (967 17 70-08)	1.5 to 4.5 inches	10 MPH	61 inches	61 inches (H) by 67 inches (W) by 76 inches (L) and 790 pounds	5 gallons of gasoline	Kawasaki, 23 HP	11 gauge	23 by 10.5 inches - 12 inches
RedMax CZTX Series CZT54X (967 67 17-01)	1 to 5 inches	11 MPH	54 inches	73 inches (H) by 67.5 inches (W) by 81 inches (L) and 1,260 pounds	11 gallons of gasoline	Kawasaki, 25.5 HP	7 gauge	23 by 10.5 inches - 12 inches
RedMax CZTX Series CZT60X (967 67 18-01)	1 to 5 inches	12 MPH	60 inches	73 inches (H) by 76 inches (W) by 81 inches (L) and 1,320 pounds	11 gallons of gasoline	Kawasaki, 27 HP	7 gauge	24 by 12 inches - 12 inches
RedMax CZTX Series CZT72X (967 94 35-01)	1 to 5 inches	12 MPH	72 inches	73 inches (H) by 85 inches (W) by 81 inches (L) and 1,448 pounds	11 gallons of gasoline	Kawasaki, 31 HP	7 gauge	24 by 12 inches - 12 inches
RedMax CZT Series CZT52 (967 67 13-01)	1.5 to 4.5 inches	10 MPH	52 inches	72 inches (H) by 67 inches (W) by 75.5 inches (L) and 760 pounds	5 gallons of gasoline	Kawasaki, 23 HP	11 gauge	23 by 9.5 inches - 12 inches
RedMax CZT Series CZT61 (967 67 14-01)	1.5 to 4.5 inches	10 MPH	61 inches	72 inches (H) by 76 inches (W) by 75.5 inches (L) and 790 pounds	5 gallons of gasoline	Kawasaki, 23 HP	11 gauge	23 by 10.5 inches - 12 inches
RedMax CZTL Series CZT54L (967 94 36-01)	1.5 to 5.5 inches	10 MPH	54 inches	73 inches (H) by 67.5 inches (W) by 81 inches (L) and 1,215 pounds	11 gallons of gasoline	Kawasaki, 23.5 HP	10 gauge	23 by 10.5 inches - 12 inches
RedMax CZTL Series CZT60L (967 94 37-01)	1.5 to 5.5 inches	10 MPH	60 inches	73 inches (H) by 76 inches (W) by 81 inches (L) and 1,172 pounds	11 gallons of gasoline	Kawasaki, 24.5 HP	10 gauge	23 by 10.5 inches - 12 inches

*The dimensions reflected here are with the rollover protective structure up and chute down.



You could lose half your customers to dandelions.

Up to 50 percent* of customers who call to complain about dandelions cancel their service. Protect their lawns, and your business, with Defendor® specialty herbicide. It works when nothing else does. Apply Defendor in early spring or late fall to stop dandelions, clover and other broadleaf weeds before they cost you a client. That way, the next time your phone rings, you'll be saying hello to more business. Learn more at www.FewerCallbacks.com.

Defendor[®]
SPECIALTY HERBICIDE



*Jefferson Davis, 2012

**Trademarks of Dow AgroSciences, DuPont or Pioneer, and their affiliated companies or their respective owners. State restrictions on the sale and use of Defendor apply. Consult the label before purchase or use for full details. Always read and follow label directions.
©2018 Dow AgroSciences LLC T38-900-007 (12/18) BR DATOTURF5061

Visit www.greenindustrypros.com/21049162

Kubota Tractor Corporation

Kubota added three new electronic fuel injection (EFI) models to its Z700 Series zero-turns, which are equipped with a wide operator station and a premium adjustable suspension seat for comfort and reduced fatigue during long jobs.



MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS & WEIGHT*	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
Z100 Series	1.5 to 4.25 inches	8 MPH forward; 4 MPH reverse	42, 48 or 54 inches	Mid-mount zero-turn	77.5 inches (L) by 42.5, 48.5 or 54.5 inches (W) by 65 inches (H) and 850 pounds	4.3 gallons	Briggs & Stratton, Kohler or Kawasaki, 21 to 25 HP	Fabricated and welded	23 by 10.5 inches - 12 inches
Z400 Series	1.5 to 5 inches	10 MPH forward; 5 MPH reverse	48, 54 or 60 inches	Mid-mount zero-turn	80.9 inches (L) by 48.5, 54.5 or 60.5 inches (W) by 69.9 inches (H) and 870 pounds	6.8 gallons	Kawasaki, 22 to 24 HP	Fabricated and welded	23 by 10.5 inches - 12 inches
Z700 Series	1 to 5 inches	11.2 MPH forward; 5.6 MPH reverse	48, 54 or 60 inches	Mid-mount zero-turn	83.9 inches (L) by 48.5, 54.5 or 60.5 inches (W) by 69.9 inches (H) and 1,232 pounds	11.6 gallons	Kohler or Kawasaki, 23.5 to 26 HP	Fabricated and welded	23 by 10.5 inches - 12 inches
ZD1000 Series	1 to 5 inches	9 MPH forward; 5 MPH reverse	54, 60 or 72 inches	Mid-mount zero-turn	88.6 inches (L) by 54.5, 60.5 or 72.5 inches (W) by 74.4 inches (H) and 1,725 pounds	5.8 gallons	Kubota, 21.6 HP	Fabricated and welded	23 by 10.5 inches - 12 inches
ZD1200 Series	1 to 5 inches	10.6 MPH forward; 5.3 MPH reverse	60 or 72 inches	Mid-mount zero-turn	93.7 inches (L) by 60.5 or 72.5 inches (W) by 78.7 inches (H) and 1,744 pounds	13.1 gallons	Kubota, 24.8 HP	Fabricated and welded	23 by 10.5 inches - 12 inches
ZD1500 Series	1 to 5 inches	10.6 MPH forward; 5.3 MPH reverse	60 or 72 inches	Mid-mount zero-turn	104.7 inches (L) by 60.5 or 72.5 inches (W) by 78.7 inches (H) and 2,028 pounds	13.1 gallons	Kubota, 30.8 HP	Fabricated and welded	23 by 10.5 inches - 12 inches
Z200 Series	1 to 5 inches	9 MPH forward; 5 MPH reverse	48, 54 or 60 inches	Mid-mount zero-turn	83.9 inches (L) by 48 inches (W) by 69.9 inches (H) and 1,720 pounds	7.4 gallons	Kubota, 27 HP	Fabricated and welded	23 by 10.5 inches - 12 inches
Z300 Series	1 to 5 inches	10.6 MPH forward; 5.3 MPH reverse	60 inches	Mid-mount zero-turn	87.8 inches (L) by 60.5 inches (W) by 75.4 inches (H) and 1,742 pounds	12.7 gallons	Kubota, 27 HP	Fabricated and welded	23 by 10.5 inches - 12 inches

*The dimensions reflected here are with the rollover protective structure and chute up.



PERFORMANCE ADVANTAGE COMPANY

TRADITION - SAFETY - VALUE

For Information On Our Complete Line Of Tool & Equipment Mounting Products, Give Us A Call @

888-514-0083

These Are Just A Few Of The Mounting Solutions We Have For Your Service Truck Or Utility Trailer

- Canister & Fuel Storage Needs



- Chain Saw & Power Saws



- Shovels,
- Sledge Hammers,
- Axe & Rake Mounts,
- All Long Handle Tools



Check Out Our Full Product Catalog & A Listing Of Our Authorized PAC Distributors At:

PACTOOLMOUNTS.COM

Visit www.greenindustrypros.com/21022972

Walker Manufacturing

With the ability to run 36- to 56-inch decks, the Walker S18 zero-turn is ideal for residential properties, gated yards and demanding customers.



MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS & WEIGHT	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
S18	0 to 4 inches	7.4 MPH	36 to 48 inches	Front-mount zero-turn	46.5 inches (H) by 43.25 inches (W) by 89.25 inches (L) and 827 pounds	4 gallons of gasoline	Vanguard, 18 HP	All-welded unitized steel	18 by 7 inches - 8 inches
C19	0 to 4 inches	6.5 MPH	36 to 56 inches	Front-mount zero-turn	47.5 inches (H) by 43.25 inches (W) by 89.25 inches (L) and 925 pounds	4 gallons of gasoline	Kohler, 19 HP	All-welded unitized steel	18 by 8.5 inches - 10 inches
C19i	0 to 4 inches	6.5 MPH	36 to 62 inches	Front-mount zero-turn	47.5 inches (H) by 43.25 inches (W) by 89.25 inches (L) and 930 pounds	4 gallons of gasoline	Kohler, 19 HP	All-welded unitized steel	18 by 8.5 inches - 10 inches
D21d	0 to 4 inches	6.5 MPH	36 to 74 inches	Front-mount zero-turn	50 inches (H) by 49.25 inches (W) by 93 inches (L) and 1,178 pounds	4.7 gallons of diesel	Kubota, 21 HP	All-welded unitized steel	18 by 9.5 inches - 8 inches
T23	0 to 4 inches	6.5 MPH	36 to 74 inches	Front-mount zero-turn	50 inches (H) by 49.25 inches (W) by 93 inches (L) and 1,009 pounds	4.7 gallons of gasoline	Kohler, 22.5 HP	All-welded unitized steel	18 by 9.5 inches - 8 inches
T25i	0 to 4 inches	6.5 MPH	36 to 74 inches	Front-mount zero-turn	50 inches (H) by 49.25 inches (W) by 93 inches (L) and 1,006 pounds	4.7 gallons of gasoline	Kohler, 25 HP	All-welded unitized steel	18 by 9.5 inches - 8 inches
T30i	0 to 4 inches	6.5 MPH	36 to 74 inches	Front-mount zero-turn	50 inches (H) by 49.25 inches (W) by 93 inches (L) and 1,039 pounds	4.7 gallons of gasoline	Kohler, 30 HP	All-welded unitized steel	18 by 9.5 inches - 10 inches
B18	0 to 4 inches	8 MPH	36 to 56 inches	Front-mount zero-turn	39 inches (H) by 49 inches (W) by 90.25 inches (L) and 790 pounds	4 gallons of gasoline	Vanguard, 18 HP	All-welded unitized steel	18 by 8.5 inches - 10 inches
B19	0 to 4 inches	8 MPH	36 to 56 inches	Front-mount zero-turn	39 inches (H) by 49 inches (W) by 90.25 inches (L) and 789 pounds	4 gallons of gasoline	Kohler, 19 HP	All-welded unitized steel	18 by 8.5 inches - 10 inches
B23i	0 to 4 inches	8 MPH	36 to 74 inches	Front-mount zero-turn	39 inches (H) by 49 inches (W) by 90.25 inches (L) and 797 pounds	4.7 gallons of gasoline	Kohler, 22.5 HP	All-welded unitized steel	18 by 8.5 inches - 10 inches
B25p	0 to 4 inches	8 MPH	36 to 74 inches	Front-mount zero-turn	40.5 inches (H) by 49 inches (W) by 90.25 inches (L) and 829 pounds	7.9 gallons of propane	Kohler, 25 HP	All-welded unitized steel	18 by 8.5 inches - 10 inches
H24d	0 to 5 inches	10 MPH	52 to 74 inches	Front-mount zero-turn	36.625 inches (H) by 66 inches (W) by 107 inches (L) and 1,434 pounds	9.4 gallons of diesel	Kohler, 23.7 HP	All-welded unitized steel	22 by 10.5 inches - 12 inches
H27i	0 to 5 inches	10 MPH	52 to 74 inches	Front-mount zero-turn	46.5 inches (H) by 66 inches (W) by 107 inches (L) and 1,185 pounds	9.4 gallons of gasoline	Kohler, 26.5 HP	All-welded unitized steel	22 by 10.5 inches - 12 inches
H37i	0 to 5 inches	10 MPH	52 to 74 inches	Front-mount zero-turn	46.5 inches (H) by 66 inches (W) by 108 inches (L) and 1,215 pounds	9.4 gallons of gasoline	Vanguard, 37 HP	All-welded unitized steel	22 by 10.5 inches - 12 inches

TRUFUEL®

THE ORIGINAL ENGINEERED FUEL



**PRECISION BLENDED
READY TO USE**



**RELIABLE STARTUP
BURNS CLEAN
RUNS CLEAN**



**ETHANOL-FREE
FOR EXTENDED
STORAGE CAPABILITIES**

Find Your TruFuel Distributor
@ TruFuel50.Com

Now available in larger containers.

Visit www.greenindustrypros.com/21049161

Gravely

MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	OVERALL DIMENSIONS & WEIGHT	APPROXIMATE BLADE SPEED	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
991230	1.5 to 5 inches	8.5 MPH forward; 4 MPH reverse	48 inches	81 inches (L) by 50 inches (W) by 49 inches (H) and 924 pounds	17,500 FPM	5 gallons	Kawasaki, 22 HP	10-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 22 by 10.5 inches - 12 inches
991232	1.5 to 5 inches	8.5 MPH forward; 4 MPH reverse	52 inches	81 inches (L) by 55 inches (W) by 49 inches (H) and 932 pounds	17,500 FPM	5 gallons	Kawasaki, 22 HP	10-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 22 by 10.5 inches - 12 inches
991234	1.5 to 5 inches	8.5 MPH forward; 4 MPH reverse	60 inches	81 inches (L) by 63 inches (W) by 49 inches (H) and 953 pounds	17,500 FPM	5 gallons	Kawasaki, 23.5 HP	10-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 22 by 12 inches - 12 inches
991128	1.5 to 5.5 inches	10 MPH forward; 5 MPH reverse	48 inches	78.5 inches (L) by 50 inches (W) by 48 inches (H) and 1,062 pounds	18,000 FPM	10 gallons	Kawasaki, 22 HP	7-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
991129	1.5 to 5.5 inches	10 MPH forward; 5 MPH reverse	52 inches	78.5 inches (L) by 55.5 inches (W) by 48 inches (H) and 1,079 pounds	18,000 FPM	10 gallons	Kawasaki, 22 HP	7-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
991132	1.5 to 5.5 inches	10 MPH forward; 5 MPH reverse	52 inches	78.5 inches (L) by 55.5 inches (W) by 48 inches (H) and 1,068 pounds	18,000 FPM	10 gallons	Kohler, 23 HP	7-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
991135	1.5 to 5.5 inches	10 MPH forward; 5 MPH reverse	52 inches	78.5 inches (L) by 55.5 inches (W) by 48 inches (H) and 1,073 pounds	18,000 FPM	10 gallons	Kohler EFI, 22 HP	7-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
991130	1.5 to 5.5 inches	10 MPH forward; 5 MPH reverse	60 inches	78.5 inches (L) by 63 inches (W) by 48 inches (H) and 1,121 pounds	18,000 FPM	10 gallons	Kawasaki, 23.5 HP	7-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
991133	1.5 to 5.5 inches	10 MPH forward; 5 MPH reverse	60 inches	78.5 inches (L) by 63 inches (W) by 48 inches (H) and 1,110 pounds	18,000 FPM	10 gallons	Kohler, 25 HP	7-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
991136	1.5 to 5.5 inches	10 MPH forward; 5 MPH reverse	60 inches	78.5 inches (L) by 63 inches (W) by 48 inches (H) and 1,115 pounds	18,000 FPM	10 gallons	Kohler EFI, 25 HP	7-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
991140	1.5 to 5.5 inches	10 MPH forward; 5 MPH reverse	60 inches	78.5 inches (L) by 63 inches (W) by 48 inches (H) and 1,136 pounds	18,000 FPM	10 gallons	Yamaha, 26 HP	7-gauge fabricated deck	Front: 13 by 6.5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
992268	1.5 to 5.5 inches	13 MPH forward; 6 MPH reverse	52 inches	80 inches (L) by 55.5 inches (W) by 47.75 inches (H) and 1,302 pounds	18,000 FPM	13.4 gallons	Kawasaki, 27 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
992267	1.5 to 5.5 inches	13 MPH forward; 6 MPH reverse	60 inches	80 inches (L) by 63 inches (W) by 47.75 inches (H) and 1,322 pounds	18,000 FPM	13.4 gallons	Kohler, 25 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
992269	1.5 to 5.5 inches	13 MPH forward; 6 MPH reverse	60 inches	80 inches (L) by 63 inches (W) by 47.75 inches (H) and 1,336 pounds	18,000 FPM	13.4 gallons	Kawasaki, 27 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
992272	1.5 to 5.5 inches	13 MPH forward; 6 MPH reverse	60 inches	80 inches (L) by 63 inches (W) by 47.75 inches (H) and 1,332 pounds	18,000 FPM	13.4 gallons	Kohler EFI, 29 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
992281	1.5 to 5.5 inches	13 MPH forward; 6 MPH reverse	60 inches	80 inches (L) by 63 inches (W) by 47.75 inches (H) and 1,355 pounds	18,000 FPM	13.4 gallons	Yamaha EFI, 29 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
992296	1.5 to 5.5 inches	13 MPH forward; 6 MPH reverse	60 inches	80 inches (L) by 63 inches (W) by 47.75 inches (H) and 1,355 pounds	18,000 FPM	13.4 gallons	Yamaha, 27.5 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
992270	1.5 to 5.5 inches	13 MPH forward; 6 MPH reverse	72 inches	80 inches (L) by 75 inches (W) by 47.75 inches (H) and 1,410 pounds	18,000 FPM	13.4 gallons	Kawasaki, 31 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
992273	1 to 5.5 inches	13 MPH forward; 6 MPH reverse	52 inches	80 inches (L) by 55.5 inches (W) by 47.75 inches (H) and 1,326 pounds	18,000 FPM	13.4 gallons	Kawasaki 27, HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
992282	1 to 5.5 inches	13 MPH forward; 6 MPH reverse	52 inches	80 inches (L) by 55.5 inches (W) by 47.75 inches (H) and 1,332 pounds	18,000 FPM	13.4 gallons	Yamaha EFI, 29 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches
992275	1 to 5.5 inches	13 MPH forward; 6 MPH reverse	60 inches	80 inches (L) by 63 inches (W) by 47.75 inches (H) and 1,358 pounds	18,000 FPM	13.4 gallons	Kawasaki, 35 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
992278	1 to 5.5 inches	13 MPH forward; 6 MPH reverse	60 inches	80 inches (L) by 63 inches (W) by 47.75 inches (H) and 1,360 pounds	18,000 FPM	13.4 gallons	Kohler EFI, 33 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
992283	1 to 5.5 inches	13 MPH forward; 6 MPH reverse	60 inches	80 inches (L) by 63 inches (W) by 47.75 inches (H) and 1,356 pounds	18,000 FPM	13.4 gallons	Yamaha EFI, 33 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
992276	1 to 5.5 inches	13 MPH forward; 6 MPH reverse	72 inches	80 inches (L) by 75 inches (W) by 47.75 inches (H) and 1,453 pounds	18,000 FPM	13.4 gallons	Kawasaki, 35 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
992284	1 to 5.5 inches	13 MPH forward; 6 MPH reverse	72 inches	80 inches (L) by 75 inches (W) by 47.75 inches (H) and 1,445 pounds	18,000 FPM	13.4 gallons	Yamaha EFI, 33 HP	7-gauge fabricated deck	Front: 15 by 6 inches - 6 inches; Rear: 24 by 12 inches - 12 inches



JOHN DEERE

RUN WITH A 3E SERIES TRACTOR

BECAUSE IT'S TIME TO TURN THIS LAND INTO YOUR LAND.

Transforming your property has never been easier. The 3E Series unlocks your land's potential with a best in class turning radius, intuitive operator station, and features that let you swap out attachments in no time. And with a 6-Year Limited Powertrain Warranty, we've got you covered from the ground up.

Nothing Runs Like A Deere™ | Run With Us
Search "John Deere 3E Series" for more



Visit www.greenindustrypros.com/10155839

From tool belts to outlets
to fixtures that shine.
Every part plays a part.

Find them all at  **ZORO.com**



The Toro Company

Toro Z Master zero-turns feature the MyRIDE suspension system, so operators can adjust their ride setting to match their personal preferences.



MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	APPROXIMATE BLADE SPEED	FUEL CAPACITY	ENGINE	TIRES
Z Master 3000 Series (with specs based on 72-inch cutting deck)	1 to 5.5 inches	10 MPH	48, 52, 60 or 72 inches	Zero-turn	18,300 FPM	8 gallons of gasoline	Kohler Command Pro, 25 HP	24 by 12 inches - 12 inches
Z Master 5000 Series (with specs based on 72-inch cutting deck)	1 to 5.5 inches	10 MPH	48, 52, 60 or 72 inches	Zero-turn	18,500 FPM	12 gallons of gasoline (or propane)	Kohler Command Pro EFI, 26.5 HP	24 by 12 inches - 12 inches
Z Master 6000 Series (with specs based on 72-inch cutting deck)	1 to 5.5 inches	11.5 MPH	52, 60 or 72 inches	Zero-turn	18,500 FPM	12 gallons of gasoline	Kohler Command Pro EFI, 34 HP	24 by 12 inches - 12 inches
Z Master 7000 Series Diesel (with specs based on 72-inch deck)	1.5 to 5 inches	11.2 MPH	52, 60 or 72 inches	Zero-turn	18,500 FPM	12 gallons of diesel	Kubota Diesel, 25 HP	24 by 12 inches - 12 inches
Z Master 7500-D (with specs based on 96-inch deck)	1 to 5.5 inches	12.5 MPH	52, 60 or 72 or 96 inches	Zero-turn	18,100 FPM	12.5 gallons of diesel	Yanmar Diesel, 37 HP	26 by 12 inches - 12 inches

Mean Green Mowers

The EVO-72 electric zero-turn mower boasts the lowest center of gravity of any 72-inch zero-turn on the market, according to Mean Green, performing staunchly on both level terrain and sloping hills.



MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS*	APPROX. BLADE SPEED	ENERGY CAPACITY	HORSEPOWER	CONSTRUCTION	TIRES
CXR-52	1 to 5.5 inches	9 MPH	52 inches	Mid-mount zero-turn	74 inches (L) by 54 inches (W) by 69 inches (H)	18,200 FPM	Lithium battery options from more than 2 to up to 7 hours	36 HP	Lightweight aerospace 7-gauge steel and aluminum	Pneumatic tires or airless MICHELIN TWEELS
CXR-60	1 to 5.5 inches	9 MPH	60 inches	Mid-mount zero-turn	74 inches (L) by 61 inches (W) by 69 inches (H)	18,500 FPM	Lithium battery options from more than 2 to up to 7 hours	36 HP	Lightweight aerospace 7-gauge steel and aluminum	Pneumatic tires or airless MICHELIN TWEELS
EVO-72	1 to 5.5 inches	13 MPH	72 inches	Mid-mount zero-turn	88 inches (L) by 74 inches (W) by 68 inches (H)	18,200 FPM	Lithium battery options from 5 to up to 10 hours	44 HP	Lightweight aerospace 7-gauge steel and aluminum	Pneumatic tires or airless MICHELIN TWEELS

*The dimensions reflected here are with the rollover protective structure.

Billy Goat's High Performing Spring Renovation!



PLUGGR

25" & 30" Hydro-Drive Self-Propelled Aerators

- Variable aeration density
- In-ground turning
- Common controls - feather speed with intuitive fingertip control

Full line of aerators include 18 - 25 & 30" reciprocating, 19" drum; 48 & 60" towables

18" Hydro-Drive Sod Cutter

- Cutting blade's laser clad hardened leading edge offers 3x blade life
- Simplest cut & drive set up in its class
- Variable speed fingertip drive for unmatched cut control & productivity

Self-Propelled Overseeder

- Blade design and laser cladding improves slicing, reduces thatch pick-up & extends blade life
- Floating cutting head
- Auto Drop™ saves seed

NEW! LASER CLAD BLADES FOR 3X BLADE LIFE!



Take the chore out of the chore with Billy Goat!

POWERED BY VANGUARD

POWERED BY HONDA

www.billygoat.com

Visit www.greenindustrypros.com/10155710

Hustler Turf Equipment

The Super Z HyperDrive zero-turn from Hustler features an exclusive HyperDrive transmission system, industrial-grade slipper piston pumps, a large oil reservoir and heavy-duty wheel motors.



MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS & WEIGHT	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
X-ONE	1 to 5.5 inches	10.5 MPH	60 inches	Side discharge	71.6 inches (H) and 1,245 pounds	11.7 gallons	Kawasaki FX 850, 27 HP	10 gauge	24 by 12 inches - 12 inches
Super Z	1 to 5.5 inches	14 MPH	60 inches	Side discharge	71.5 inches (H) and 1,451 pounds	11.7 gallons	Kawasaki FX 850, 27 HP	7 gauge	24 by 12 inches - 12 inches
Super Z HyperDrive	1 to 5.5 inches	16 MPH	60 inches	Side discharge	71.5 inches (H) and 1,536 pounds	11.7 gallons	Vanquard M61 EFI, 37 HP	7 gauge	26 by 12 inches - 12 inches
Super 104	1 to 5.5 inches	11 MPH	104 inches	Rear discharge	71.5 inches (H) and 2,500 pounds	12 gallons	Vanquard M61 EFI, 37 HP	11 gauge	26 by 12 inches - 12 inches
Super S	1.5 to 5.5 inches	9 MPH	60 inches	Stand-on side discharge	47.83 inches (H) and 1,055 pounds	6.5 gallons	Kawasaki FX 730, 23.5 HP	10 gauge	20 by 12 inches - 10 inches

BigDog Mower Company

MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS & WEIGHT	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
Diablo	1 to 5.5 inches	10.5 MPH	60 inches	Side discharge	72.5 inches (H) and 1,465 pounds	11.7 gallons	Kawasaki FX 850, 27 HP	10 gauge	24 by 12 inches - 12 inches
Diablo MP	1 to 5.5 inches	14 MPH	60 inches	Side discharge	72.5 inches (H) and 1,475 pounds	12 gallons	Kawasaki FX 850, 27 HP	10 gauge	26 by 12 inches - 12 inches

Progressive Casualty Ins. Co. & Affiliates. Business and Workers' Compensation coverage provided and serviced by affiliated and third party insurers.

Small business is no small task.

So Progressive offers commercial auto and business insurance that makes protecting yours no big deal.

Local Agent | ProgressiveCommercial.com

PROGRESSIVE
COMMERCIAL

Visit www.greenindustrypros.com/10915742

John Deere

The John Deere Z994R zero-turn is powered by a three-cylinder, liquid-cooled Final Tier 4 diesel engine; the high-torque, low-emission engine provides power with low vibration and noise levels.



MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS & WEIGHT	APPROXIMATE BLADE SPEED	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
Z915E	1 to 5.5 inches	10 MPH	60 inches	Riding zero-turn	84 inches (L) by 62, 68 or 74 inches (W) and 1,100 to 1,178 pounds	18,000 FPM	11.5 gallons of gasoline	Kohler, 25 HP	Deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z920M	1 to 5.5 inches	10 MPH	60 inches	Riding zero-turn	84 inches (L) by 62, 68 or 74 inches (W) and 1,220 to 1,283 pounds	18,000 FPM	11.5 gallons of gasoline	Kawasaki, 23.5 HP	7-Iron PRO mowing deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z925M EFI Flex Fuel	1 to 5.5 inches	10 MPH	54 or 60 inches	Riding zero-turn	84 inches (L) by 68 or 74 inches (W) and 1,198 to 1,291 pounds	18,000 FPM	11.5 gallons of gasoline	Kohler, 25 HP	7-Iron PRO mowing deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z930M	1 to 5.5 inches	10 MPH	54 or 60 inches	Riding zero-turn	84 inches (L) by 68 or 74 inches (W) and 1,275 to 1,365 pounds	18,000 FPM	11.5 gallons of gasoline	Kawasaki, 25.5 HP	7-Iron PRO mowing deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z945M EFI	1 to 5.5 inches	10 MPH	60 inches	Riding zero-turn	84 inches (L) by 74 inches (W) and 1,275 to 1,365 pounds	18,000 FPM	11.5 gallons of gasoline	Kohler, 27 HP	7-Iron PRO mowing deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z950M	1 to 5.5 inches	10 MPH	60 or 72 inches	Riding zero-turn	84 inches (L) by 74 or 86 inches (W) and 1,275 to 1,365 pounds	18,000 FPM	11.5 gallons of gasoline	Kawasaki, 27 HP	7-Iron PRO mowing deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z955M EFI	1 to 5.5 inches	10 MPH	60 or 72 inches	Riding zero-turn	84 inches (L) by 74 or 86 inches (W) and 1,275 to 1,365 pounds	18,000 FPM	11.5 gallons of gasoline	Kohler, 29 HP	7-Iron PRO mowing deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z960M	1 to 5.5 inches	10 MPH	60 or 72 inches	Riding zero-turn	84 inches (L) by 74 or 86 inches (W) and 1,252 to 1,340 pounds	18,000 FPM	11.5 gallons of gasoline	Kawasaki, 31 HP	7-Iron PRO mowing deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z930R	1 to 5.5 inches	12 MPH	54 or 60 inches	Riding zero-turn	84 inches (L) by 68 or 74 inches (W) and 1,273 to 1,310 pounds	18,000 FPM	11.5 gallons of gasoline	Kawasaki, 25.5 HP	7-Iron PRO mowing deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z950R	1 to 5.5 inches	12 MPH	54 or 60 inches	Riding zero-turn	84 inches (L) by 74 or 86 inches (W) and 1,292 to 1,340 pounds	18,000 FPM	11.5 gallons of gasoline	Kawasaki, 27 HP	7-Iron PRO mowing deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z970R	1 to 5.5 inches	12 MPH	60 or 72 inches	Riding zero-turn	84 inches (L) by 74 or 86 inches (W) and 1,336 to 1,345 pounds	18,000 FPM	11.5 gallons of gasoline	Kawasaki, 35 HP	7-Iron PRO mowing deck made from one piece of stamped steel	24 by 12 inches - 12 inches
Z994R Diesel	1 to 5.5 inches	10.5 MPH	54 or 60 inches	Riding zero-turn	88.6 inches (L) by 68 or 74 inches (W) and 1,660 to 1,720 pounds	18,000 FPM	11.5 gallons of diesel or biodiesel (up to B20)	Yanmar, 24.7 HP	Deck made from one piece of stamped steel	24 by 12 inches - 12 inches four-ply
Z997R Diesel	1 to 5.5 inches	11.5 MPH	60 or 72 inches	Riding zero-turn	96 inches (L) by 74 or 86 inches (W) and 1,774 to 1,841 pounds	18,000 FPM	11.5 gallons of diesel or biodiesel	Yanmar, 37.4 HP	7-Iron PRO mowing deck made from one piece of stamped steel	26 by 12 inches - 12 inches square-shoulder four-ply

Snapper Pro

The Snapper Pro SS200 zero-turn runs on a powerful Vanguard 810cc electronic fuel injection engine with Oil Guard technology to extend oil change intervals up to 500 hours.



MODEL NUMBER	CUTTING HEIGHT RANGE	MOWING SPEED	DECK DIMENSIONS	MOWER CONFIGURATION	OVERALL DIMENSIONS & WEIGHT	APPROXIMATE BLADE SPEED	FUEL CAPACITY	ENGINE	CONSTRUCTION	TIRES
S200xt	1.5 to 5 inches	10 MPH forward; 5 MPH reverse	61 inches	Zero-turn	79 inches (L) by 76 inches (W) and 1,190 pounds	17,600 to 18,500 FPM	5 gallons of gasoline	Briggs & Stratton Commercial Series, 27 HP	iCD Cutting System with heavy-gauge steel	Front: 13 by 6.5 inches - 6 inches; Rear: 24 by 12 inches - 12 inches
S150xt	1.5 to 5 inches	10 MPH forward; 5 MPH reverse	52 inches	Zero-turn	78 inches (L) by 68 inches (W) and 1,141 pounds	17,600 to 18,500 FPM	10 gallons of gasoline	Kawasaki FX730V, 23.5 HP	iCD Cutting System with heavy-gauge steel	Front: 13 by 6.5 inches - 6 inches; Rear: 24 by 9.5 inches - 12 inches
S125xt	1.5 to 5 inches	10 MPH forward; 5 MPH reverse	52 inches	Zero-turn	81 inches (L) by 67.5 inches (W) and 1,059 pounds	17,600 to 18,500 FPM	5.5 gallons of gasoline	Kawasaki FS691V, 23 HP	iCD Cutting System with heavy-gauge steel	Front: 13 by 5 inches - 6 inches; Rear: 22 by 11 inches - 10 inches
S50xt	1.5 to 4.5 inches	8 MPH forward; 4 MPH reverse	36 inches	Zero-turn	69 inches (L) by 52 inches (W) and 688 pounds	17,600 to 18,500 FPM	8 gallons of gasoline	Kawasaki FX600V, 19 HP	Fabricated 10-gauge, double top deck and double-reinforced side skirts	Front: 11 by 4 inches - 5 inches; Rear: 20 by 7 inches - 10 inches
S40	1.5 to 4.5 inches	8 MPH forward; 4 MPH reverse	48 inches	Zero-turn	80 inches (L) by 62.5 inches (W) and 753 pounds	17,600 to 18,500 FPM	5.5 gallons of gasoline	Kawasaki FR651V, 21.5 HP	Fabricated 10-gauge, double top deck and double-reinforced side skirts	Front: 11 by 4 inches - 5 inches; Rear: 20 by 10 inches - 10 inches
SS100	1.75 to 5 inches	8 MPH forward; 4 MPH reverse	36 inches	Stand-on zero-turn	63.5 inches (L) by 48.5 inches (W) and 765 pounds	17,600 to 18,500 FPM	6 gallons of gasoline	Kawasaki FX600V, 19 HP	Fabricated 10-gauge	Front no-flats: 11 by 4 inches - 5 inches; Rear: 23 by 8.5 inches - 12 inches
SS200	1.75 to 5 inches	10 MPH forward; 5 MPH reverse	52 inches	Stand-on zero-turn	67 inches (L) by 65 inches (W) and 921 pounds	17,600 to 18,500 FPM	8 gallons of gasoline	Vanguard 810cc EFI, 28 HP	iCD Cutting System with heavy-gauge steel	Front no-flats: 13 by 5 inches - 6 inches; Rear: 23 by 10.5 inches - 12 inches



STIHL[®]



#1 Brand Among
Landscape
Professionals
in America*



**THERE'S ONLY
ONE NUMBER ONE.***

Your Business is Our Business.

Our quality manufacturing and superior service do more than help us sell equipment. Both have helped us earn the trust and loyalty of America's hardest workers. People like the landscapers at Bud Jones and Sons, Inc., who for years, have chosen powerful, reliable STIHL products to maintain their customers' beautiful landscapes and grow their business. Landscapers like them are why STIHL has been the number one selling brand of gasoline-powered handheld outdoor power equipment among U.S. professional landscapers since 2007.*

Visit your local STIHL dealer today and start powering up your business.

To find a STIHL dealer: STIHLdealers.com

For product information: STIHLusa.com

**"Number one selling brand" claim based on 2007-2018 syndicated Irwin Broh research of the U.S. professional landscaper market. ©2019 STIHL



STIHL[®]

Visit www.greenindustrypros.com/10155925